

## Product Description

This sleek and modern luminaire has been designed to handle any environment. With a beautiful slimline design, along with high performance lumen output, this versatile fixture can be used as a flood or an area light. Including a multitude of mounting types, surge protection, motion sensor and photocell options, and the most advanced LED on the market, this fixture has everything, including an incredible 120,000 hour lifespan.

> Standard Ship Product - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Philips Lumileds Luxeon 3030 2D LEDs with high efficacy up to 140 Lm/W
- Dimming by PWM, Resistance, or 1-10V with 3' attached cable whip
- National listing lab tested with multiple distributions
- PMMA clear lens for durability and clarity with optic over each LED
- Tool-free bottom mount door hinge allows easy access
- Designed for harsh temperature and high humidity
- Solid state with high shock and vibration resistance
- Instant on and off without delay or re-strike
- Industrial cold forged 1070 pure aluminum anodized fixture housing
- Smooth electrophoresis surface treatment finish with stainless hardware
- Excellent resistance to corrosion, UV degradation and abrasion
- Choice of mounting to poles or walls with trunnion, slipfitter and arm options
- Includes integrated gasketed NEMA twistlock receptacle
- Bi-level option for optional photocell and motion sensor
- 3 foot attached power cord whip for quick and easy installation
- High CRI - RA>80 enhances original colors
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- No lead, mercury, UV or IR radiation
- Short circuit, over current, over voltage, over temp protection
- Operating temperature: -40 to 55 degrees celsius
- IP66 rated for outdoor applications
- Over 120,000 hour LED life
- Certifications: CE, RoHS, RCM, FCC, TUV, CB, IK10, cUL, UL, DLC
- 5 year system warranty

## EXITE PL SERIES

Affordable Solution with Multiple Mounting Options  
**Low Profile LED Dimmable Luminaire**



TR - 180 Degree Adjustable Trunnion



SF - 180 Degree Adjustable Slipfitter



U - Large Adjustable Yoke Bracket



EA - Arm Mount for Wall or Pole

## Models:

- VVDAF080 - 80W - 11393 Lm - 16.9" (L) x 12" (W) x 3.5" (H) - 8.4 Lbs - EPA 0.23
- VVDAF100 - 100W - 13678 Lm - 16.9" (L) x 12" (W) x 3.5" (H) - 8.4 Lbs - EPA 0.23
- VVDAF150 - 150W - 21828 Lm - 16.9" (L) x 12" (W) x 3.5" (H) - 8.4 Lbs - EPA 0.23
- VVDAF185 - 185W - 25561 Lm - 16.9" (L) x 12" (W) x 3.5" (H) - 8.4 Lbs - EPA 0.23
- VVDAF240 - 240W - 33771 Lm - 23.4" (L) x 12" (W) x 3.6" (H) - 13 Lbs - EPA 0.42
- VVDAF300 - 300W - 42549 Lm - 23.4" (L) x 12" (W) x 3.6" (H) - 15.3 Lbs - EPA 0.42
- VVDAF400 - 400W - 56932 Lm - 30.2" (L) x 13.4" (W) x 4.1" (H) - 25 Lbs - EPA 0.58
- VVDAF500 - 500W - 69616 Lm - 30.2" (L) x 13.4" (W) x 4.1" (H) - 25 Lbs - EPA 0.58

## Ordering Information:

Part Number:

\*Adder Applies. Extended Lead Time May Apply.

Ordering Example: VVDP10-50-T2M-UNV-BZ-ND-TR

Family	CCT	Optic	Voltage	Finish	Dimming	Mounting	Accessories*
VVDAF080 VVDAF100 VVDAF150 VVDAF185 VVDAF240 VVDAF300 VVDAF400 VVDAF500	30 - 3000K 40 - 4000K 50 - 5000K 57 - 5700K 65 - 6500K	T2M - Type II Medium T3S - Type III Short T3M - Type III Medium T4M - Type IV Medium T5M - Type V Medium N1 - NEMA 5x6 (90x120 Degrees) N2 - NEMA 3x3 (30 Degrees)	UNV1 - 100-277V UNV2 - 347-480V*	BZ - Bronze RAL 7022  CS - Custom*	ND - No Dim D1 - 1-10V PWM - PWM RD - Resistance DL - Dali*	TR - Trunnion SF - Slipfitter U - Large Yoke EA - Wall or Pole Arm  See mounting dimensions & details on the website	PC - NEMA Photocell SC - Shorting Cap MS - Motion Sensor Up to 25' with 120 Degree Motion Range SP - 10KV Surge Protection PC6 - 6.5' Power Cord Extension with IP65 Connector (Field Installed) PG - US Grounded Plug



Vivid Leds, Inc.  
 PO BOX 9  
 Sellersburg, IN 47172  
 800-974-3570  
 www.vividleds.us

Dimensions, specifications, and  
 product pictures are subject to  
 change without notice.

A4