

## Product Description

The Decora SF series is a perfect solution for outdoor parking lot, area lighting or flood applications. The body offers a slim, aerodynamic design with superb system efficacy, heat radiation ability, and endurance for brutal working environments. Replacing up to 1000W HID, the Aero PL has quickly become the luminaire of choice for retrofitting existing applications.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Philips Lumileds Luxeon 3030 LEDs with high efficacy >130 Lm/W
- Integrated dimming 1-10V standard
- Excellent heat dissipation design for optimum efficiency
- National listing lab tested with IES standards
- Patented design with architectural appearance
- Advanced Meanwell HLG power supply - field replaceable
- Solid State with high-shock and vibration resistance
- Instant on and off without delay or re-strike
- Anodized aluminum radiator with anti-static coating
- Industrial die cast anodized aluminum fixture housing
- Fishbone style high efficiency heatsink
- Smooth bronze polyester powdercoat finish with stainless hardware
- Excellent resistance to corrosion, UV degradation and abrasion
- Mitsubishi polycarbonate shatterproof cover for enhanced safety
- Excellent optical presentation for multiple applications
- Rubber gasket LED ring ensures IP waterproofing
- Mounts with integrated adjustable slipfitter 2 3/8" O.D.
- Photocell adaptable with knockout
- 2.5 foot attached power cord whip
- High CRI - RA>70 enhances all original colors
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- No lead, mercury, UV or IR radiation
- Short circuit, over current, over voltage, over temp protection
- Low Tj for best lumen depreciation and extended life span
- Operating temperature: -40 to 50 degrees celsius
- Power factor: >0.95
- IP66 rated for outdoor applications
- 100,000 hour LED life
- Certifications: CE, RoHS, UL, cUL, DLC
- 5 year system warranty

## DECORA SF SERIES

Ultra Thin with Slipfitter Mounting Option  
LED Dimmable Luminaire



## Models:

- VDAK150: 150W - 19602 Lm - 22" (L) x 11" (W) x 3" (D) - 13 Lbs - EPA 1.22
- VDAK265: 265W - 32638 Lm - 25" (L) x 14" (W) x 3" (D) - 19 Lbs - EPA 1.83

Dimensions and EPA include slipfitter



<b>Ordering Information:</b>				Part Number:			
Ordering Example: VDAK150P-50-T4M-UNV-BZ-A-D1							
Family	CCT	Optic	Voltage	Finish	Mounting	Dimming	Accessories
VDAK150P VDAK265P	50 - 5000K	T4M - 130x70 Type IV	UNV - 100-277V	BZ - Bronze	A - Slipfitter	D1 - 1-10V Dim	



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
800-974-3570  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

A6