

## Product Description

With a high performance heat sink, exceptional lumen maintenance, and a rock solid housing, the Exite Elite will last for many years to come. With a variety of color temperatures and optics, this luminaire can be used in arenas, gymnasiums, airport runways, high mast, shipping ports, or general flood lighting.

> Standard Ship Product - 30 Day Lead Time

|              |  |       |
|--------------|--|-------|
| Project:     |  | Type: |
| Location:    |  |       |
| Prepared By: |  | Date: |
| Comments:    |  |       |

## Performance Summary

- Osram LEDs with high efficacy up to 130 Lm/W
- Integrated dimming by PWM, Resistance, DALI or 1-10V
- National listing lab tested with multiple Type V distributions
- PMMA shatterproof clear lens cover for durability and clarity
- Unique micro optic over each LED reduces glare and enhances uniformity
- Designed for harsh temperature and high humidity
- Solid state with high shock and vibration resistance
- Instant on and off without delay or re-strike
- Industrial cold forged 1070 pure aluminum anodized fixture housing
- Smooth electrophoresis surface treatment finish with stainless hardware
- Excellent resistance to corrosion, UV degradation and abrasion
- Stainless steel hardware to ensure long life
- Heavy duty 240 degree adjustable surface mount yoke bracket
- Horizontal and vertical angle indicators allow mounting adjustment in increments of 10 degrees
- Optional laser guide with bracket for precise aiming is easy to install and remove
- Thermal management by a seamless link of heatsink vents
- Ultra low EMI noise generation eliminates electrical interference
- Integrated 10KV line-to-ground and line-to-line surge protection wired and included
- Field installed aluminum visor included
- 6.5' attached power cord whip and 4' dimming cable for quick and easy installation
- High CRI - RA>70 enhances original colors
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- No lead, mercury, UV or IR radiation
- Integrated Meanwell driver features short circuit, over current, over voltage & temp protection
- Operating temperature: -40 to 55 degrees celsius
- IP66 washdown rated for indoor or outdoor applications
- Over 100,000 hour LED life
- Certifications: CE, RoHS, ENEC, SAA, ETL, DLC
- 5 year system warranty

## EXITE ELITE SERIES

Intense Output For Multiple Applications  
LED Dimmable Luminaire




Integrated Laser Guide Accessory



## Models:

- VDSP600W - 600W - 80732 Lm - 57 Lbs - EPA 2.2
- VDSP750W - 750W - 99496 Lm - 62 Lbs - EPA 2.2
- VDSP1000W - 1000W - 133915 Lm - 68 Lbs - EPA 2.2
- VDSP1250W - 1250W - 164110 Lm - 73 Lbs - EPA 2.2\*\*



240 DEGREE ROTATION



## Ordering Information:

Part Number:

\*Adder Applies

Ordering Example: VDSP600W-40-T51-UNV1-BK-ND-YK

| Family   | CCT  | Optic  | Voltage                             | Finish                         | Dimming   | Accessories*   |
|--|--|--|-------------------------------------|--------------------------------|---|--|
| VDSP600W<br>VDSP750W<br>VDSP1000W<br>VDSP1250W | 30 - 3000K<br>40 - 4000K<br>50 - 5000K<br>57 - 5700K<br>65 - 6500K | T51 - Type V 15 Degree<br>T52 - Type V 20 Degree<br>T53 - Type V 25 Degree<br>T54 - Type V 40 Degree | UNV1 - 100-277V<br>UNV2 - 277-480V* | BK - Black/Red<br>CS - Custom* | ND - No Dim<br>D1 - 1-10V Dim<br>PWM - PWM Dim<br>RD - Resistance Dim<br>DL - Dali Dim* | <b>PCE</b> - AC Power Cord Extension with IP65 Connector<br><b>PG1</b> - 120V Grounded Plug<br><b>PG2</b> - 277V NEMA Twist Lock Plug<br><b>LG</b> - Integrated Laser Guide For Precise Aiming<br><b>SC</b> - 10' Safety Cable<br><b>EB</b> - External Ballast Box For Remote Mounting<br><b>LVE</b> - Low Voltage Power Cord Extension with IP65 Connector For External Ballast Box (Max 19') |




Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
800-974-3570  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

\*\*Uses Two External Driver Boxes. Box size is 15" (L) x 10.5" (W) x 3.75" (H). Standard low voltage cable from fixture to box is 88", attached by a waterproof connector. The AC cable on the driver box is 78". Max low voltage distance is 19'.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.



B2

Revised 5.30.18