
Product Description

The Industry series is a ARRA compliant wall mount luminaire using the latest Samsung LEDS. From benchmarking a minimum 104 degree F ambient during thermal testing, to custom designed LED arrays for each luminaire individually, to using the best housing materials and coatings, each aspect has been taken into careful consideration to ensure many years of trouble-free service.

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

Performance Summary

- · Samsung LEDS with high efficacy >125 Lm/W
- USA assembled product with quick warranty support
- Standard design with modern components, excellent choice for retrofitting
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Tupe III or Type V optic
- · High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- · Clear borosilicate flat glass lens for reduced hot spots
- · A360 extruded ingot die-cast housing with hinged full cutoff front frame
- DuPont textured architectural bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- · Custom housing colors available upon request
- 1/2" coin plugs with o-rings for conduit and photocell
- Cast-in template for mounting directly over a 4" recessed outlet box
- Accessible to mount by 1/2" surface conduit
- Rust resistant stainless steel hardware with durable nickel-plating
- · Fin heatsinks for best heat dissipation and long life
- High CRI RA>80 enhances original colors
- 1-10V dimmable driver with surge protection and battery backup option
- Fast turn on with no warm up or cold start issues
- · Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 213,000 hour LED life @ L70 tested at 25 degrees celsius
- · Certifications: CE, RoHS, CSA IP65 outdoor rated
- 5 year system warranty



Models:

VVDWPC15FR: 37W - 4764 Lm - 525mA - B:2, U:2, G:0

Ordering Information:				Part Number:		
*Adder Applies **Adder Applies. Extended Lead Time May A				Apply. Ordering Example: VVDWPC15FR-50-S5C-V27-BZ-ND		
Family	ССТ	Optic	Voltage	Finish	Dimming	Accessories*
WDWPC15FR	30 - 3000K** 40 - 4000K** 50 - 5000K 1 - 290nm*	SSC - Type V Short 115 Degree Clear Flat Glass Lens S3S - Type III Short* Clear Flat Glass Lens	V27 - 120-277V	BZ - Bronze CS - Custom*	ND - Non Dim DM - 1-10V Dim	SF - Single Fuse DF - Double Fuse SP - 20kA Surge Protection 120-277VAC EM - Emergency Driver Provides 90 Minutes of Backup Power PC1 - Button Photocell 120V PC2 - Button Photocell 250-305V WG - Stainless Steel Wire Guard RG - Clear Polycarbonate Vandal Resistant Guard



Vivid Leds, Inc. Sellersburg, IN 47172 800-974-3570 www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

> Quick Ship - In Stock, Ready to Ship

Medium Full Cutoff Glass Lens Wall Pack

LED Dimmable Luminaire