

Product Description

The Focus series is a architectural wall luminaire providing up AND down lighting with a wide distribution designed to replace HID lighting systems up to 70w. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 8 to 16 feet can be achieved.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Samsung LEDs with high efficacy >105 Lm/W
- USA assembled product with quick warranty support
- Standard design with modern components, excellent choice for retrofitting
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Type III optic
- High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Tempered clear flat glass lens on top and bottom
- A360 extruded ingot die-cast housing with hinged full cutoff front frame
- DuPont textured architectural bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- Custom housing colors available upon request
- Mounts directly over a 4" recessed outlet box or use 1/2" surface conduit
- Rust resistant stainless steel hardware with durable nickel-plating
- Fin heatsinks for best heat dissipation and long life
- High CRI - RA>80 enhances original colors
- 1-10V dimmable driver with surge protection
- Fast turn on with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 410,000 hour LED life @ L70 tested at 25 degrees celsius
- Certifications: CE, RoHS, CSA - IP65 outdoor rated
- 5 year system warranty

FOCUS UD SERIES

Glass Lens Up / Down Crescent Wall Sconce
LED Dimmable Luminaire



Models:

- VDWDP34Q: 32W - 3387 Lm - 16W Up and 16W Down - 525mA - B:1, U:5, G:1

Ordering Information:				Part Number:		
*Adder Applies				Ordering Example: VDWDP34Q-50-T5-V27-BZ-ND		
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories*
VDWDP34Q	30 - 3000K** 40 - 4000K** 50 - 5000K	T5 -Type V Clear Flat Glass	V27 - 120-277V	BZ - Bronze CS - Custom*	ND - Non Dim DM - 1-10V Dim	SF - Single Fuse DF - Double Fuse SP - 20kA Surge Protection 120-277VAC PC1 - Button Photocell 120V PC2 - Button Photocell 250-305V



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

D17

Revised 3.24.18