

Product Description

The Connect series is a unique harsh environment LED luminaire when a low profile surface mount fixture is needed. The Connect Wet series allows for connectivity between the fixtures to minimize power cords for a clean look. With mounting and wire connection hardware included, everything you need is in one complete package.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		


Performance Summary

- Lumenmax 2835 LED with excellent efficacy >110 Lm/W
- Fixtures can connect together with included 3.25' connect cable
- Mounting clips with hardware and 3.25' detachable power cord whip included
- Up to 200W can be connected on one run
- Solid state LED light source, instant start, long life
- National listing lab tested with Type V 120 degree distribution
- Maximum lumen output with utilization of clear lens
- Smooth, non-glare and decorative with frosted lens
- Effectively illuminates ambient light with superior foot candles
- Patented design with 1.3mm aluminum housing with excellent heat dissipation
- Durable IK10 casing with high purity AL6063 aluminum heatsink
- Aluminum LED boards with copper tracings for best thermal management
- High shock and vibration resistant with rivets on the aluminum LED board
- V-O flame rated and corrosion proof polycarbonate cover
- High quality silica gel end caps with aviation grade waterproof plugs
- Quick clip on surface mount kit provides easy installation
- Universal 100-277V integral driver with surge protection
- Silent operation, no noise, no flickering
- No infrared or UV radiation
- Contains no mercury or lead and cool to the touch
- Excellent CRI RA>82 for color enhancement
- Power factor: >0.90, THD<20%
- Operating temperature: -25 to 50 degrees celsius
- 100,000 hour LED lamp life
- Certifications: CE, RoHS, TUV, SAA, ETL, DLC, IP65, IK10
- 3 year system warranty

CONNECT WET MINI SERIES

Linear Fixtures Connect in a Series

LED Outdoor Luminaire



IK10 LOAD BEARING



WEATHERPROOF



CORROSION PROOF

Models:

- WDT5SLW0600: 2' - 15W - 1800 Lm - 23.3"(L) x 1.7"(W) x 1.5"(H)
- WDT5SLW0900: 3' - 25W - 3000 Lm - 35.2"(L) x 1.7"(W) x 1.5"(H)
- WDT5SLW1200: 4' - 30W - 3600 Lm - 46.9"(L) x 1.7"(W) x 1.5"(H)
- WDT5SLW1500: 5' - 40W - 4800 Lm - 60.1"(L) x 1.7"(W) x 1.5"(H)
- WDT5SLW1800: 6' - 44W - 5280 Lm - 71.8"(L) x 1.7"(W) x 1.5"(H)
- WDT5SLW2400: 8' - 60W - 7200 Lm - 91.6"(L) x 1.7"(W) x 1.5"(H)

Quick and Easy Installation

Two mounting clips with screws included with each unit

Power cord and linkable cord included with each unit



Ordering Information:		Part Number:			
*Adder Applies			Ordering Example: WDT5SLW0600-30-UNV-CL-SM		
Family	CCT	Voltage	Lens	Mounting	Accessories*
WDT5SLW0600 WDT5SLW0900 WDT5SLW1200 WDT5SLW1500 WDT5SLW1800 WDT5SLW2400	30 - 3000K 40 - 4000K 50 - 5000K 60 - 6000K	UNV - 100-277V	CL - Clear FR - Frosted (Diffused)	SM - Surface Mount Clip	GP - 6.5' Power Cord with Grounded Plug CC - Custom Length Connect Cord CP - Custom Length Power Cord Whip



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F10