

Product Description

The Connect series is a unique harsh environment LED luminaire when a low profile surface mount fixture is needed. The Connect Wet series allows for connectivity between the fixtures to minimize power cords for a clean look. With mounting and wire connection hardware included, everything you need is in one complete package.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Lumenmax 2835 LED with excellent efficacy >110 Lm/W
- Fixtures can connect together with included 40" connect cable
- Mounting clips with hardware and 40" detachable power cord whip included
- Quick clip on surface mount kit provides easy installation
- NCF on suspension mounting clip for retrofitting fluorescent fixtures
- Suspension option includes a 3' aircraft cable that can be cut to length
- Dustproof and waterproof IP65 design
- Up to 200W can be connected on one run
- Solid state LED light source, instant start, long life
- National listing lab tested with Type V 120 degree distribution
- Smooth, non-glare and decorative with frosted lens
- Effectively illuminates ambient light with superior foot candles
- Patented design with 1.3mm aluminum housing with excellent heat dissipation
- Durable plastic casing with high purity AL6063 aluminum heatsink
- Aluminum LED boards with copper tracings for best thermal management
- High shock and vibration resistant with rivets on the aluminum LED board
- High quality silica gel end caps with aviation grade waterproof plugs
- Universal 100-277V integral driver with surge protection
- Silent operation, no noise, no flickering
- No infrared or UV radiation
- Contains no mercury or lead and cool to the touch
- Excellent CRI RA>82 for color enhancement
- Power factor: >0.95, THD<19%
- UGR: >19
- Operating temperature: -30 to 50 degrees celsius
- 100,000 hour LED lamp life
- Certifications: CE, RoHS, TUV, SAA, ETL, DLC, IP65
- 3 year system warranty

CONNECT WET NCF SERIES

Linear Fixtures Connect in a Series


LED Outdoor Luminaire



Quick and Easy Installation

Two mounting clips with screws included with each unit

Power cord and DIY connectors included with each unit



Models:

- WVDSF90LNCF20: 2' - 20W - 2400 Lm - 25.9" (L) x 3.5"(W) x 2.4"(H)
- WVDSF90LNCF30: 3' - 30W - 3600 Lm - 36.5" (L) x 3.5"(W) x 2.4"(H)
- WVDSF90LNCF40: 4' - 40W - 4800 Lm - 48.2" (L) x 3.5"(W) x 2.4"(H)
- WVDSF90LNCF50: 5' - 50W - 6000 Lm - 60.1" (L) x 3.5"(W) x 2.4"(H)



WATERPROOF PLUGS

Ordering Information:

Part Number:

*Adder Applies

**Available in select models only

Ordering Example: WVDSF90LNCF20-30-CS-SM-40-40

Family	CCT	Lens	Mounting	Connect Cord	Power Cord	Accessories*
WVDSF90LNCF20 WVDSF90LNCF30 WVDSF90LNCF40 WVDSF90LNCF50	30 - 3000K 40 - 4000K 50 - 5000K 60 - 6000K	FR - Frosted (Diffused)	SM - Surface Mount Clips NCF - NCF Suspension Clips*	40 - 40 inch 80 - 80 Inch*	40 - 40 inch whip 80 - 80 Inch whip*	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F12

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

Revised 10.10.18