

Product Description

The Connect series is a unique harsh environment LED luminaire when a low profile surface mount fixture is needed. The Connect Wet series allows for connectivity between the fixtures to minimize power cords for a clean look. With mounting and wire connection hardware included, everything you need is in one complete package.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Lumenmax 2835 LED with excellent efficacy >110 Lm/W
- Unique patented V-shape design for an incredible 270 degree coverage
- Dramatically improves the look of any food or merchandise being displayed
- Ultimate solution for coolers when combined with a motion sensor
- National listing lab tested with Type V degree distribution
- Fixtures can connect together with included in/out 30" connect cables
- Mounting clips with hardware and 30" power cord whip included
- Moisture ready with IP65 dustproof and waterproof design
- Up to 200W can be connected on one run
- Solid state LED light source, instant start, long life
- Maximum lumen output with utilization of clear lens
- Effectively illuminates ambient light with superior foot candles
- Quick clip on surface mount kit provides easy installation
- Patented design with 1.3mm aluminum housing with excellent heat dissipation
- Food safe an shatterproof plastic casing with high purity AL6063 aluminum heatsink
- Aluminum LED boards with copper tracings for best thermal management
- High shock and vibration resistant with rivets on the aluminum LED board
- High quality silica gel end caps with waterproof plugs
- Tested LED binning for color uniformity
- Universal 100-277V integral driver with surge protection
- Silent operation, no noise, no flickering
- No infrared or UV radiation
- Contains no mercury or lead and cool to the touch
- Excellent CRI RA>82 for color enhancement
- Power factor: >0.95, THD<19%
- Operating temperature: -30 to 50 degrees celsius
- 100,000 hour LED lamp life
- Certifications: CE, RoHS, TUV, SAA, ETL, DLC, IP65
- 3 year system warranty

CONNECT WET COOL SERIES

Linear Fixtures Connect in a Series
LED Cooler Luminaire



Models:

- WVD8DL1222C: 4' - 22W - 2640 Lm - 47.2" (L) x 1.6"(W) x 1.7"(H)
- WVD8DL1525C: 5' - 25W - 3000 Lm - 59.1" (L) x 1.6"(W) x 1.7"(H)
- WVD8DL1828C: 6' - 28W - 3360 Lm - 70.9" (L) x 1.6"(W) x 1.7"(H)

Quick and Easy Installation

Three mounting clips with screws included with each unit

Power cord and linkable cord included with each unit



Ordering Information:			Part Number:			
*Adder Applies			**Available in select models only		Ordering Example: WVD8DL1222C-30-CL-SM-30-30	
Family	CCT	Lens	Mounting	Connect Cord	Power Cord	Accessories*
WVD8DL1222C WVD8DL1525C WVD8DL1828C	30 - 3000K 40 - 4000K 50 - 5000K 60 - 6000K	CL - Clear	SM - Surface Mount Clips	30 - 30 inch	30 - 30 inch	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F13