

Product Description

The Connect series is a unique indoor environment LED luminaire when a low profile surface mount fixture is needed. The Connect Dry series allows for connectivity between the fixtures to minimize power cords for a clean look. With mounting and wire connection hardware included, everything you need is in one complete package.

> Standard Ship - 30 Day Lead Time


Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Lumenmax 2835 LED with excellent efficacy >110 Lm/W
- Fixtures can connect together with included joint plug or 10" connect cable
- Mounting clips with hardware and 10" power cord whip included
- Male / Female joint plug for seamless light connection with no dark spot
- Up to 200W can be connected on one run
- TRIAC dimming option for enhanced control
- Solid state LED light source, instant start, long life
- National listing lab tested with Type V 120 degree distribution
- Maximum lumen output with utilization of clear lens
- Smooth, non-glare and decorative with frosted lens
- Well distributed light using a patented reflecting system
- Effectively illuminates ambient light with superior foot candles
- Patented design with 0.8mm aluminum housing with excellent heat dissipation
- Durable casing with high purity AL6063 aluminum heatsink
- High quality Polystyrene cover with strong capacity
- Delicate shape, lightweight, easy installation
- Quick clip on surface mount, magnet mount or suspension kit options
- Universal 100-277V integral driver with surge protection
- Silent operation, no noise, no flickering
- No infrared or UV radiation
- Contains no mercury or lead and cool to the touch
- Excellent CRI RA>82 for color enhancement
- Power factor: >0.90, THD<20%
- Operating temperature: -25 to 50 degrees celsius
- 100,000 hour LED lamp life
- Certifications: CE, RoHS, TUV, SAA, ETL, DLC - IP40
- 3 year system warranty

CONNECT DRY LPH SERIES

Linear Fixtures Connect in a Series
Dimmable LED Indoor Luminaire



Quick and Easy Installation

Two mounting clips with screws included with each unit

Power cord and linkable cord included with each unit



Models:

- WDT8DL0600: 2' - 9W - 945 Lm - 22.4"(L) x 1.6"(W) x 1.7"(H)**
- WDT8DL0900: 3' - 13W - 1365 Lm - 34.5"(L) x 1.6"(W) x 1.7"(H)**
- WDT8DL1200: 4' - 18W - 1890 Lm - 46.5"(L) x 1.6"(W) x 1.7"(H)**
- WDT8DL1500: 5' - 25W - 2625 Lm - 58.3"(L) x 1.6"(W) x 1.7"(H)
- WDT8DL1800: 6' - 30W - 3150 Lm - 68.7"(L) x 1.6"(W) x 1.7"(H)
- WDT8DL2400: 8' - 44W - 4620 Lm - 92.8"(L) x 1.6"(W) x 1.7"(H)

Ordering Information:			Part Number:		
Family	CCT	Voltage	Lens	Mounting	Accessories*
WDT8DL0600 WDT8DL0900 WDT8DL1200 WDT8DL1500 WDT8DL1800 WDT8DL2400	30 - 3000K 40 - 4000K 50 - 5000K 60 - 6000K	UNV - 100-277V	CL - Clear CS - Clear Striated FR - Frosted (Diffused)	SM - Surface Mount Clip MC - Magnetic Clip* SK - Suspension Kit*	GP - 3.3' Power Cord with Grounded Plug TR - TRIAC Dimming 120V Only** OF - On/Off Switch CC - Custom Length Connect Cord CP - Custom Length Power Cord Whip



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F7