Product Description

The Maize series is an exceptional product with a track record of 7 years in the field. We use the latest technology and continue to raise the bar in terms of housing quality, lamp efficacy, and overall extended lifespan. Using only top quality components such as Rubycon capacitors, flame retardant materials, a water resistant cover, and LG LEDS, the Maize series is a market leader for commercial applications.

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

Performance Summary

- LG 5630 SMD LED with high efficacy >130 Lm/W
- · Most realistic HID lamp available
- · National listing lab tested with IES standards
- Excellent solution for retrofitting HID or incandescent lamps
- IP65 rated for indoor or outdoor use exposed to the elements
- · Internal driver for easy installation
- Fast turn on, no warm up or cold start problems
- · Integrative LED design for heatsink and housing
- Advanced heatsink dissipates heat without a fan
- Suitable for totally enclosed fixtures
- Polycarbonate lens cover provides dust and water protection
- · Crystal clear lens for maximum lumen output
- · Diffused lens reduces glare and enhances appearance
- Rubycon capacitance power for best protection
- · Contains no mercury or lead and cool to the touch
- · No infrared or UV radiation
- Generates low heat, reducing your HVAC loads
- Flame retardant housing material
- High CRI RA>80 enhances original colors
- · Beam angle: 360 degrees
- Power factor: >.95
- · Operating temperature: -29 to 60 degrees celsius
- · 100,000 hour LED life
- · Certifications: CE, PSE, TUV, RoHS, SAA, cUL, UL, DLC
- 1 year system warranty

Models:

- VVD631T: 96 LEDS 30W 3900Lm 10.1" (L) x 3.27" (D)
- WD632T: 132 LEDS 40W 5200 Lm 10.1" (L) x 3.27" (D)
- VVD633T: 168 LEDS 50W 6500 Lm 10.1" (L) x 3.27" (D)

MAIZE TULIP SERIES

> Standard Ship - 30 Day Lead Time





Ordering Information:				Part Number:		
*DLC not available for E26 Medium Base					Ordering Example: VVD631T-30-T5-UNV-E26-CL	
Family	ССТ	Optic	Voltage	Base Type	Lens Cover	
VVD631T VVD632T VVD633T	30 - 3000K 40 - 4000K 50 - 5000K 57 - 5700K	T5 - Type V 360 Degree	UNV - 100-277V	E26 - Medium* E39 - Mogul EX39 - Mogul	CL - Clear DF - Diffused	

IP65 Waterproof Design



Vivid Leds, Inc. PO BOX 9 Sellersburg, IN 47172 800-974-3570 www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Cautions:

Flame Retardant Material

Remove ballast before installing Check dimensions of lamp for fitment

