Product Description

The Twilight series is the leader in the industry for an economical color changing luminaire. Sticking to the basics by using industry standard DMX protocal for control, to clever wiring, to internal self-control with built-in programs, the Twilight series offers a basic solution that applies to even the most difficult applications. With quality throughout, from the LEDS to the die-cast housing, the Twilight shines above the rest.

Performance Summary

- Edison LEDS with RGB efficacy >35 Lm/W and white >80 Lm/W**
- High powered 3W LEDS for long light throw
- Solid state with high shock and vibration resistance
- · Dimming capability with DMX or built-in controller
- Each red, green & blue LED has a 256 color depth
- Precise optics with photometric lens built over each LED
- Ground mounted attached base secures with two bolts
- Easy installation and aiming with 120 degree rotating bracket
- RGB color changing modes by DMX 512 controller
- Fixture modes: 1) Independant, 2) DMX, 3) Master/Slave
- LED screen with push button control to change programs or setup DMX
- · Built-in self-control with pre-programmed lighting effects
- Programs include solid colors, flashing, fading, color jumping
- High vertical illuminance for large space lighting
- Extruded 6063 aluminum & iron silver housing with low heat generation
- Durable polycarbonate clear cover with water resistant protection
- Natural convection cooling method
- Light lens is 30% brighter than ordinary lens
- 5' power cord whip & 1.5' in and out IP68 DMX cables included
- Contains no mercury or lead and cool to the touch
- No infrared or UV radiation
- Operating temperature: -20 to 40 degrees celsius
- IP65 rated, applicable for indoor or outdoor applications
- Universal voltage: 120 VAC
- 100,000 hour LED life
- Certifications: CE, RoHS, ETL
- 1 year system warranty 2 or 3 year optional

Models:

- WDZ736B: 36 LEDS 95W 10.6" x 12.6" x 11.8" 24.3 Lbs
- WVDZ772B: 72 LEDS 180W 15.7" x 12.6" x 11.8" 35.3 Lbs Static color or white - 36/72 LEDS RGB rotating LEDS - R:12/24, G:12/24, B:12/24

Ordering Information:

*Adder Applies					Ordering Example: WD736B-RGB-10-UNV-SG-BS	
Family	ССТ	Optic	Voltage	Finish	Mounting	Accessories*
WDZ736B WDZ772B	RGB - RGB Color Changing W - Static White - 3000K N - Static White - 4300K C - Static White - 6000K R - Static Gred - 625nm G - Static Green - 525nm B - Static Blue - 460nm Y - Static Yellow/Amber - 590nm	10 - 10 Degree* 15 - 15 Degree 30 - 30 Degree 45 - 45 Degree	120 - 120 VAC	SG - Silver Gray CS - Custom*	GB - Ground Base	GP - Field Installed Grounded Plug DMX Cables DMX Controllers Wireless DMX Signal Amplifiers

11.8"



Vivid Leds, Inc. PO BOX 9 Sellersburg, IN 47172 800-974-3570 www.vividleds.us

2 Dimensions, specifications, and product pictures are subject to change without notice.

www.vividleds.us change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

> Standard Ship - 30 Day Lead Time

TWILIGHT Z7 SERIES

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	





**80 Lm/W is based on 6000K white CCT. Static color or RGB LEDS > 35 Lm/W.

60

10.6" / 15.7

J13 Revised 6.15.19