

Product Description

Nicolaudie is a manufacturer of industry standard DMX lighting control software and hardware products for all architectural applications. Every single interface is made for a specific installation. Once integrated with one of the compatible software packages, it is possible to easily control the lighting within a variety of places such as homes, hotels, restaurants, fountains, gardens, commercial and many more applications.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- DMX USB Software Controller
- Free Nicolaudie software to download
- Powerful and user friendly software interface
- Internal SD card saves the memory when power is off
- Build your own light information or use presets
- Compatible with ESA and/or ESA2 Easy Stand Alone software
- Easy Stand Alone push button controls on device
- Three switch buttons for scene selection and dimming
- Setup operating effect for each step
- Setup program operation pause time
- Programming connection with USB 2.0 or IP depending on model
- Works with PC/MAC, 32/64 bit
- 8 contact dry trigger ports
- Mini USB power connector and 120V power adapter included
- Operating temperature: 0 to 60 degrees celsius
- IP20 rated, applicable for indoor applications
- Certifications: EC, EMC, RoHS, ETL, UL
- 1 year system warranty

KONTROL SLESA SERIES

Easy Stand Alone Operates Without Computer
LED DMX Architectural Software Control



SLESAU9

Complete easy-to-read instruction manual included

Models:

- WDSLESAU9: Entry Level USB Version
1 Universe, 256 DMX Channels, 20 Scenes, 20K Stand Alone Memory, 1200 Memory with 20 Channels, 440 Memory with 60 Channels
- WDSLESAU8: USB Version
1 Universe, 512 DMX Channels, 255 Scenes, 128K Stand Alone Memory, 5600 Memory with 20 Channels, 2100 Memory with 60 Channels, Clock Triggering
- WDSLESAUE7: USB + Ethernet Version
3 Universes, 2x512 DMX Channels, 250 Scenes, microSD Stand Alone Memory, Unlimited Memory Capacity, Clock Triggering
- WDSLESAIP1: IP Version (No USB)
1 Universe, 512 DMX Channels, 255 Scenes, 128K Stand Alone Memory, 5629 Memory with 20 Channels, 2109 Memory with 60 Channels, Clock Triggering



SLESAU8

NICOLAUDIE ●●●

Ordering Information:

Part Number:

*Adder Applies

Ordering Example: WDSLESAU9-UNV-BL

Family	Voltage	Finish	Accessories*
WDSLESAU9 WDSLESAU8 WDSLESAUE7 WDSLESAIP1	UNV - 120 VAC Power Adapter	BL - Blue	DMX Cables Wireless DMX Signal Amplifiers



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

L1

Revised 6.1.17