

Product Description

The Orion series cables are a commercial grade solution for mobile or permanent wiring in harsh conditions. The IP68 connectors, used with our Twilight fixtures, offer the same quality watertight connector as our luminaires.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Packaged Cable Features

- Commercial grade DMX or 0-10V cables for RGB fixtures
- DMX cable is 22AWG, UL2464, 128net, 3-pin in a black insulated sleeve
- DMX cable rated at 80 degrees Celsius, 300VW-1, 6mm connector diameter
- 0-10V cable is 18AWG, SVT temperature resistant, 2-pin in a black insulated sleeve
- 0-10V cable rated at 105 degrees Celsius, copper core, 7mm connector diameter
- Specifically designed for any professional lighting control setup
- IP68 features quality PVC LLT twist-lock connectors
- All cable lengths are male to female with included connector
- A terminator is suggested for the end of the DMX fixture run

Models:

- WD11908FR - 3' IP68 DMX Cable
- WD11909FR - 6' IP68 DMX Cable
- WD11910FR - 10' IP68 DMX Cable
- WD11911FR - 17' IP68 DMX Cable
- WD11912FR - 33' IP68 DMX Cable
- WD11913FR - 50' IP68 DMX Cable
- WD11915FR - 65' IP68 DMX Cable
- WD11916FR - 80' IP68 DMX Cable
- WD11917FR - 100' IP68 DMX Cable
- WD11914FR - IP68 DMX Terminator Male
- WDMFENDS68FR - DMX IP68 Connectors (For Bulk Cable - Pair M/F)*
- WDDMXBLKFR - Indoor/Outdoor Bulk DMX Cable - sold by the foot
- WDCONVERTFR - DMX IP68 to IP20 XLR 1' Converter Cable (Pair M/F)
- WD21908FR - 3' IP68 0-10V Cable
- WD21909FR - 6' IP68 0-10V Cable
- WD21910FR - 10' IP68 0-10V Cable
- WD21911FR - 17' IP68 0-10V Cable
- WD21912FR - 33' IP68 0-10V Cable
- WD21913FR - 50' IP68 0-10V Cable
- WD21915FR - 65' IP68 0-10V Cable
- WD21916FR - 80' IP68 0-10V Cable
- WD21917FR - 100' IP68 0-10V Cable
- WDMFENDS69FR - 0-10V IP68 Connectors (For Bulk Cable - Pair M/F)*
- WVD010BLKFR - Indoor/Outdoor Bulk 0-10V Cable - sold by the foot

ORION SIGNAL CABLE SERIES

Professional Quality DMX & 0-10V Extension Cables

Twilight Series Compatible



IP68 DMX Cable



Actual product size and look may vary slightly from pictures shown.

*Connectors require soldering.

Cautions

- Maximum DMX run is 300' or 60 fixtures and signal amplifiers are available for extended runs.
- Maximum 0-10V run is 300'. Caution should be taken not to run the cable near the power cable to avoid interference.
- For outdoor use, it is recommended to heat shrink over all connectors for a long life installation.
- A DMX terminator should be used to terminate the last fixture.
- Check local building and electrical codes before assuming these cables can be used for your project.



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

N3

Revised 4.11.18