

Product Description

The Array XP series flood light luminaire is a slim wall pack for a variety of applications including building perimeter, entrances, stairways and security lighting. It provides a low-profile architectural style with the power of bright, energy efficient LEDs. It has a rugged aluminum construction with multi-mount capabilities. 0° to +90° tilt adjustments. For a building that has a modern or futuristic look.

> Quick Ship - In Stock, Ready to Ship


Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Philips Lumileds 3030 LEDs with high efficacy >140 Lm/W
- Modern design with modern components, excellent choice for retrofitting
- Low profile, 3G vibration rated compact design prescribed by ANSI C136.31
- National listing lab tested to IES standards
- High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Rugged one-piece A360 die-cast housing with integral heat sink
- Housing is completely sealed against moisture and environmental contaminants
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Light engine is available in a 5000K (70 CRI) configuration
- Optics are precisely designed to shape the distribution, maximizing efficiency
- Tempered UV coated lens provides outstanding performance and glare control
- Architectural bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- Rust resistant stainless steel hardware with durable nickel-plating
- Cast-in template for mounting directly over a 4" recessed outlet box
- 90 minute emergency backup kit can be integrated to the fixture
- Emergency backup provides 8W and 900 lumens of illumination
- 1-10V dimmable driver included
- Fast turn on with no warm up or cold start issues
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 104 degrees F (-40 to 40 degrees C)
- 100,000 hour LED life based on LM-80 results and TM-21 calculation
- Certifications: CE, RoHS, UL, cUL, DLC - IP65 outdoor rated
- 5 year system warranty

ARRAY XP SERIES

Wall Pack
LED Dimmable Luminaire



Models:

- WDMWP1027: 27W - 3600 Lm - 7.3" (W) x 9.2" (L) x 4.2" (H) - 3.4 Lbs**
- WDMWP1040: 40W - 5200 Lm - 7.3" (W) x 9.2" (L) x 4.2" (H) - 3.9 Lbs
- WDMWP1067: 67W - 8800 Lm - 10.1" (W) x 11.1" (L) x 5.1" (H) - 7.4 Lbs
- WDMWP1080: 80W - 10500 Lm - 10.1" (W) x 11.1" (L) x 5.1" (H) - 7.8 Lbs

Ordering Information:				Part Number:		
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories*
WDMWP1027 WDMWP1040 WDMWP1067 WDMWP1080	50 - 5000K	T5 - Type V	V27 - 120-277V	BZ - Bronze	ND - Non Dim DM - 1-10V Dim*	PC - Button Photocell 100-277V EM - Emergency Backup Kit



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.