

Product Description

The Connect series is a unique harsh environment LED luminaire when a low profile surface mount fixture is needed. The Connect Wet series allows for connectivity between the fixtures to minimize power cords for a clean look. With mounting and wire connection hardware included, everything you need is in one complete package.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Lumenmax 2835 LED with excellent efficacy >110 Lm/W
- Fixtures can connect together with included 40" connect cable
- Mounting clips with hardware and 40" detachable power cord whip included
- Up to 600W can be connected on one run
- National listing lab tested with Type V 120 degree distribution
- Maximum lumen output with utilization of clear lens
- Smooth, non-glare and decorative with frosted lens
- Effectively illuminates ambient light with superior foot candles
- Patented design with 1.3mm aluminum housing with excellent heat dissipation
- Durable IK10 casing with high purity AL6063 aluminum heatsink
- High shock and vibration resistant with rivets on the aluminum LED board
- V-O flame rated and corrosion proof polycarbonate cover
- High quality silica gel end caps with aviation grade waterproof plugs
- Quick clip on surface mount kit provides easy installation
- Universal 100-277V integral driver with surge protection
- Excellent CRI RA>82 for color enhancement
- Power factor: >0.90, THD<20%
- Operating temperature: -25 to 50 degrees celsius
- 100,000 hour LED lamp life
- Certifications: CE, RoHS, TUV, SAA, ETL, DLC, IP66, IK10
- 3 year system warranty

CONNECT WET XL SERIES

Linear Fixtures Connect in a Series
LED Outdoor Luminaire



IK10 LOAD BEARING



WEATHERPROOF



CORROSION PROOF

Models:

- WDSF90L315W: 1' - 15W - 1650 Lm - 11.8" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L630W: 2' - 30W - 3300 Lm - 24.7" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L940W: 3' - 40W - 4400 Lm - 35.4" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L1240W: 4' - 40W - 4400 Lm - 47.2" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L1260W: 4' - 60W - 6600 Lm - 47.2" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L1580W: 5' - 80W - 8800 Lm - 59.1" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L1890W: 6' - 90W - 9900 Lm - 70.5" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L2490W: 8' - 90W - 9900 Lm - 94.5" (L) x 3.5"(W) x 2.4"(H)
- WDSF90L24120W: 8' - 120W - 13200 Lm - 94.5" (L) x 3.5"(W) x 2.4"(H)

Quick and Easy Installation

Two mounting clips with screws included with each unit

Power cord and linkable cord included with each unit



Ordering Information:		Part Number:				
*Adder Applies		**Available in select models only		Ordering Example: WDSF90L315W-30-CS-SM-40-40		
Family	CCT	Lens	Mounting	Connect Cord	Power Cord	Accessories*
WDSF90L315W WDSF90L630W WDSF90L940W WDSF90L1240W WDSF90L1260W WDSF90L1580W WDSF90L1890W WDSF90L2490W WDSF90L24120W	30 - 3000K 40 - 4000K 50 - 5000K 60 - 6000K	CS - Clear Striated FR - Frosted (Diffused)	SM - Surface Mount Clip	40 - 40 inch 80 - 80 Inch*	40 - 40 inch whip 80 - 80 Inch whip* 80P - 80 inch with plug*	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F11