

Product Description

The Focus VP1 series wall and ceiling mount luminaire is available with clear or opal lenses, and open, vertical half or horizontal half door frames designed to replace HID lighting systems from 400w HPS. Typical lighting applications include industrial facilities, oil, gas, painting facilities, and auto service facilities. Mounting heights of 18 to 30 feet can be used based on light level and uniformity requirements.

> Quick Ship - In Stock, Ready to Ship

| | | |
|--------------|--|-------|
| Project: | | Type: |
| Location: | | |
| Prepared By: | | Date: |
| Comments: | | |

Performance Summary

- Samsung 561B LEDs with high efficacy >150 Lm/W
- USA assembled product with quick warranty support
- Listed for vaportight applications in wet environments
- Standard design with modern components, excellent choice for retrofitting
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Type V wide 110 degree optic
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Clear or opal diffused vandal-resistant polycarbonate lens
- A360 extruded ingot die-cast housing with top frame
- 1/2" coin plugs can be tapped for conduit wiring entrance
- DuPont textured architectural powdercoat finish
- Chromate conversion coating for long lasting appearance
- Custom housing colors available upon request
- Mounts directly to a wall, conduit pendant or ceiling mount surface
- Adjustable stainless steel bracket and yoke available
- Rust resistant stainless steel hardware with durable nickel-plating
- High CRI - RA>80 enhances original colors
- 1-10V dimmable driver with surge protection option
- Fast turn on with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 187,000 hour LED life @ L70 tested at 25 degrees celsius
- Certifications: CE, RoHS, ETL, cETL - IP66 indoor or outdoor rated
- 5 year system warranty

FOCUS VP2 SERIES

Vaportight, Vandal-Resistant Linear Wall, Pendant or Ceiling Mount
LED Dimmable Luminaire



Models:

- WDV2A047: 2' - 47W - 7309 Lm
- WDV2A066: 2' - 66W - 10294 Lm
- WDV2Q112: 4' - 112W - 16287 Lm
- WDV2Q136: 4' - 136W - 19733 Lm

Ordering Information:

Part Number:

*Adder Applies

**Adder Applies. Extended Lead Time May Apply.

Ordering Example: WDV2A047-50-S5C-V27-OF-PT-DM

| Family | CCT | Optic | Voltage | Frame | Finish | Dimming | Accessories* |
|--|--|--|-----------------------------------|-----------------|-------------------------------|--------------------------------|--|
| WDV2A047 WDV2A066 WDV2Q112 WDV2Q136 | 30 - 3000K** 40 - 4000K** 50 - 5000K | S5C - Type V Wide Clear S5O - Type V Wide Opal* | V27 - 120-277V V48 - 347-480V* | OF - Open Frame | PT - Platinum CS - Custom* | ND - Non Dim DM - 1-10V Dim | SF - Single Fuse DF - Double Fuse SP - 20kA Surge Protection 120-277VAC BB - 90 Minute Battery Backup AB - Stainless Adjustable Bracket (Pair) YK - Heavy Duty Stainless Steel Yoke (Pair) QM - Stainless Quick Mount Bracket (Pair) |



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F2