

Product Description

The Connect series is a unique indoor environment LED luminaire when a low profile surface mount fixture is needed. The Connect Dry series allows for connectivity between the fixtures to minimize power cords for a clean look. With mounting and wire connection hardware included, everything you need is in one complete package.

> Standard Ship - 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Lumenmax 2835 LED with excellent efficacy >110 Lm/W
- Fixtures can connect together with included joint plug or 10" connect cable
- Mounting clips with hardware and 10" power cord whip included
- Up to 200W can be connected on one run
- Solid state LED light source, instant start, long life
- National listing lab tested with Type V 120 degree distribution
- Maximum lumen output with utilization of clear lens
- Smooth, non-glare and decorative with frosted lens
- Well distributed light using a patented reflecting system
- Effectively illuminates ambient light with superior foot candles
- Patented design with 0.8mm aluminum housing with excellent heat dissipation
- Durable casing with high purity AL6063 aluminum heatsink
- High quality Polystyrene cover with strong capacity
- Quick clip on surface mount kit provides easy installation
- Universal 100-277V integral driver with surge protection
- Silent operation, no noise, no flickering
- No infrared or UV radiation
- Contains no mercury or lead and cool to the touch
- Excellent CRI RA>82 for color enhancement
- Power factor: >0.90, THD<20%
- Operating temperature: -25 to 50 degrees celsius
- 100,000 hour LED lamp life
- Certifications: CE, RoHS, TUV, SAA, ETL, DLC - IP40
- 3 year system warranty

CONNECT DRY HP SERIES

Linear Fixtures Connect in a Series

LED Indoor Luminaire



Models:

- WDSF90L6001: 2' - 30W - 2700 Lm - 24.7" (L) x 4.1" (W) X 2.5" (H)
- WDSF90L9001: 3' - 40W - 3600 Lm - 35.4" (L) x 4.1" (W) X 2.5" (H)
- WDSF90L1201: 4' - 60W - 5400 Lm - 47.2" (L) x 4.1" (W) X 2.5" (H)
- WDSF90L1501: 5' - 80W - 7200 Lm - 59.1" (L) x 4.1" (W) X 2.5" (H)
- WDSF90L1801: 6' - 90W - 8100 Lm - 70.9" (L) x 4.1" (W) X 2.5" (H)
- WDSF90L2401: 8' - 120W - 10800 Lm - 94.5" (L) x 4.1" (W) X 2.5" (H)

Quick and Easy Installation

Two mounting clips with screws included with each unit

Power cord and linkable cord included with each unit



Ordering Information:		Part Number:				
*Adder Applies		**Available in select models only		Ordering Example: WDSF90L6001-30-CL-DM-10-10		
Family	CCT	Lens	Mounting	Connect Cord	Power Cord	Accessories*
WDSF90L6001 WDSF90L9001 WDSF90L1201 WDSF90L1501 WDSF90L1801 WDSF90L2401	30 - 3000K 40 - 4000K 50 - 5000K 60 - 6000K	CS - Clear Striated FR - Frosted (Diffused)	SM - Surface Mount Clip	10 - 10 inch 40 - 40 inch* 80 - 80 Inch*	10 - 10 inch whip 40 - 40 inch whip* 80 - 80 inch whip* 40P - 40 inch with plug*	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

F9

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

Revised 10.10.18