Product Description

The Twilight series is the leader in the industry for an economical color changing luminaire. The Twilight series offers a basic solution that applies to even the most difficult applications. With quality throughout, from the LEDS to the die-cast housing, the Twilight shines above the rest.

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

Performance Summary

- Edison LEDS with RGB efficacy >35 Lm/W and white >80 Lm/W**
- · Solid state with high shock and vibration resistance
- Each red, green & blue LED has a 256 color depth
- Precise optics with photometric lens built over each LED
- Easy installation with 180 degree rotating mounting brackets
- RGB color changing modes by any DMX 512 controller
- Dimming capability by any DMX controller
- Vandal proof with no option to alter DMX functions
- DMX coding required by Kontrol Master Pro 3 Series
- · Kontrol Master Pro 3 sold seperately, only one needed per job
- Static color or white option dimming and on/off control requires DMX
- High vertical illuminance for large space lighting
- Die-cast aluminum alloy silver housing with low heat generation
- · Corrosion resistant, durable, with high efficiency
- Durable polycarbonate clear cover with water resistant protection
- · Natural convection cooling method
- Light lens is 30% brighter than ordinary lens
- 5' power cable whip and 1.5' in and out DMX cable standard option
- 1.5' power cable in and out and 1.5' DMX cable in and out linkable option
- · Contains no mercury or lead and cool to the touch
- · No infrared or UV radiation
- · Operating temperature: -20 to 40 degrees celsius
- IP65 rated, applicable for indoor or outdoor applications
- Constant current driver with universal voltage: 100-240 VAC
- 100,000 hour LED life
- · Certifications: CE, RoHS, ETL
- \cdot 1 year system warranty 2 or 3 year optional

TWILIGHT Z3 LP SERIES

> Standard Ship - 30 Day Lead Time

Static Color, Static White or RGB Color Changing

LED Wash, Stripe or Graze



Power & DMX Linkable Option:

DMX Signal Cable with IP68 Connector



Power & DMX extension cables available on the website

Models:

• VVDZ318LP: 18 LEDS - 20W - 22" (L) - 3.5 Lbs

VVDZ336LP: 36 LEDS - 40W - 43.3" (L) - 6.6 Lbs

Static color or white - 18/36 LEDS

RGB rotating LEDS - R:6/12, G:6/12, B:6/12 LEDS



Ordering	Information:	Part Number:				
*Adder Applies				Ordering Example: VVDZ318LP-W-15-ST-SG-BB		
Family	ССТ	Optic	Connection	Finish	Mounting	Accessories*
WDZ318LP WDZ336LP	RGB - RGB Color Changing W - Static White - 3000K N - Static White - 4300K C - Static White - 6000K R - Static Red - 625nm G - Static Green - 525nm B - Static Blue - 460nm Y - Static Yellow/Amber - 590nm	10 - 10 Degree 20 - 20 Degree 45 - 45 Degree 15 - 15 x 50 Degree	ST - Standard LK - Linkable*	SG - Silver Gray CS - Custom*	BB - Bottom Bracket	GP - Field Installed Grounded Plug DMX Cables DMX Controllers Wireless DMX Signal Amplifiers



**80 Lm/W is based on 6000K white CCT. Static color or RGB LEDS > 35 Lm/W.