

Product Description

This slick and modern luminaire has been designed to handle any environment. With a beautiful slimline design, along with high performance lumen output, this versatile fixture can be used as a flood or an area light. Including a multitude of mounting types, surge protection, motion sensor and photocell options, and the most advanced LED on the market, this fixture has everything, including an incredible 120,000 hour lifespan.

> Special Order - Minimum 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Philips Lumileds LEDs with high efficacy up to 160 Lm/W
- Standard design with modern components, excellent choice for retrofitting
- Low profile, 3G vibration rated compact design minimizes wind loads
- Patented heat dissipation design for optimum efficiency
- National listing lab tested with multiple distributions
- High lumen maintenance exceeds DOE requirements
- Tool-free bottom mount door hinge allows easy access
- Designed for harsh temperature and high humidity
- Solid state with high shock and vibration resistance
- Instant on and off without delay or re-strike
- PMMA clear lens for durability and clarity
- Photometric optic built over each LED for enhanced light distribution
- Industrial cold forged die cast fixture housing
- Smooth electrophoresis surface treatment finish with stainless hardware
- Excellent resistance to corrosion, UV degradation and abrasion
- Choice of mounting to poles or walls with trunnion, slipfitter and arm options
- Includes integrated gasketed NEMA twistlock receptacle
- High CRI - RA>70 enhances original colors
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- No lead, mercury, UV or IR radiation
- 0-10V dimmable Sosen driver with integrated surge protection
- Short circuit, over current, over voltage, over temp protection
- Operating temperature: -40 to 45 degrees celsius
- IP65 rated for outdoor applications
- Over 120,000 hour LED life
- Certifications: CE, CB, ERP, RoHS, IK08, UL, DLC
- 10 year limited warranty

EXITE PL

Multiple Mounting Options

Wattage & Color Selectable LED Dimmable Luminaire



Models:

- VVDAF1 - 50/65/80/100W - 8000-16000 Lm - 12.3" (L) x 11.3" (W) x 2.5" (H) - 4.9 Lbs - EPA 0.23
- VVDAF2 - 120/150/200/240 - 19200-38400 Lm - 16.6" (L) x 12.2" (W) x 2.7" (H) - 7 Lbs - EPA 0.23
- VVDAF3 - 240/300/400/500W - 38400-80000 Lm - 26.8" (L) x 12.2" (W) x 2.8" (H) - 13.4 Lbs - EPA 0.42

Ordering Information:				Part Number:			
*Adder Applies				Ordering Example: VVDAF1-CS1-T3-UNV-BZ-ND-TR			
Family	CCT	Optic	Voltage	Finish	Dimming	Mounting	Accessories*
VVDAF1 VVDAF2 VVDAF3	CS1 - 3000K 4000K 5000K CS2 - 4000K 5000K 5700K	T2 - Type II T3 - Type III T4 - Type IV T5 - Type V	UNV1 - 100-277V UNV2 - 277-480V*	BZ - Bronze RAL 7022 CS - Custom*	ND - No Dim D1 - 0-10V	U - Yoke TR - Trunnion SF - Slipfitter* EA - Wall or Pole Arm *	PC - NEMA Photocell SC - Shorting Cap SP - 10KV Surge Protection
						See mounting dimensions & details on the website	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

A1