Product Description

The Architekt HP can be used for lawns, courtyards, pathways, roadways, and many other outdoor applicaitons. This LED post top light fixture, with its excellent optic design and die cast aluminum housing, is perfect for harsh environments. The patented cooling design aids in a LED Tj > 85C. Using Philips Lumileds LEDS and a Sosen driver, the quality is top notch.

Performance Summary

- Energy-efficient Philips Lumileds SMD LEDS with high efficacy >140 Lm/W
- USA assembled product with quick warranty support
- In stock and ships from several U.S. locations for quick delivery
- Better visibility than HID or fluorescent with crisp, white light
- Patented design with high quality components, excellent choice for retrofitting
- National listing lab tested to IES standards with Type V optic
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance 3G vibration tested
- High lumen maintenance exceeds DOE requirements
- 1/9th LED micro color binning enables tight color control
- Aviation grade die cast aluminum housing with professional black powdercoat finish
- Housing is sandblasted and polished for corrosion resistance, rust free and fadeless
- $\cdot\,$ Streamlined housing, no rough edges or scraping, with SUS316 stainless steel hardware
- $\cdot\,$ Housing and driver compartment is one piece to maximize heat dissipation
- CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- $\cdot\,$ Copper condensation valve balances the air pressure and prevents water vapor accumulation
- Cooling fins are added to the heatskink for low temperature and higher efficiency
- Shatterproof polycarbonate lens over the LEDS
- Patented double waterproofing design on the radiator and module to prevent condensation
- Advanced constant current Sosen power supply with 6KV surge protection
- Standard 2 3/8" OD pole opening at the bottom of the fixture
- Fast turn on with no warm up or cold start issues
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>70
- Operating temperature: -30 to 45 degrees celsius
- 100,000 hour LED life IP65 rated for outdoor locations
- Certifications: CE, RoHS, FCC, UL, cULus, DLC
- 10 year limited warranty

Models:

- WDWSDHPT60 60W 8010 Lm 18.9" (L) x 18.9" (W) x 18.8" (H) 12.4 Lbs
- VVDWSDHPT100 100W 13210 Lm 18.9" (L) x 18.9" (W) x 18.8" (H) 12.4 Lbs

Ordering Information:				Part Number:		
Ordering Example: WDWSDHPT60-50-T5-V27-B						
Family	ССТ	Optic	Voltage	Finish	Mounting	
VVDWSDHPT60 VVDWSDHPT100	50 - 5000K	T5 - Type V 159 Degrees	V27 - 120-277V	BK - Black	PM - Pole Top Mount	



Vivid Leds, Inc. PO BOX 9 Sellersburg, IN 47172 330-809-0431 www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

> Quick Ship - In Stock, Ready to Ship

Architekt HP

Post Top

LED Luminaire

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

