Product Description

LED Architekt FC Full CutOff Wall Pack can be widely used in indoor or outdoor lighting (wet location). Ideal for mechanical or electronic processing workshops, storage warehouses, steel mills, gas stations, toll booth, waiting rooms, the platforms of railway station, or indoor stadiums.

> Quick Ship - In Stock, Ready to Ship

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

Performance Summary

- Energy-efficient Philips Lumileds SMD LEDS with high efficacy >130 Lm/W
- In stock and ships from several U.S. locations for quick delivery
- Standard design with modern components, excellent choice for retrofitting
- Wattage selectable in 30W, 45W, 60W, and 70W outputs
- Easy access to control switch for a range of CCT's from 3000K to 5000K
- Integrated photocell provides dusk to dawn control
- National listing lab tested to IES standard
- Full cutoff design with IES Type IV forward throw optics
- · Patented design with high quality components, excellent choice for retrofitting
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- · A360 ingot die-cast aluminum alloy housing with bronze powdercoat finish
- Five stage chromate conversion coating for long lasting appearance
- Streamlined housing, no rough edges or scraping, with 304 stainless steel hardware
- · Housing and driver compartment is one piece to maximize heat dissipation
- Innovative quick mount bracket for easy, contractor friendly installation
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- LED array manufactured using a state-of-the-art SMT machine
- Shatterproof polycarbonate diffused lens over the LEDS with rubber grommet
- Serviceable constant current Sosen driver with 1-10V dimming
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>70
- Operating temperature: -22 to 114 degrees F
- 100,000 hour LED life of maintenance-free, safe operation
- IP65 rated for indoor or outdoor locations
- Certifications: CE, RoHS, FCC, UL, cUL, DLC
- 10 year limited warranty



Models:

• VVDWSDFWFC: 30W/45W/60W/70W - 8980 Lm - 3000K/4000K/5000K - 8.2" (W) x 14" (L) x 5" (H) - 6.2 Lbs - Photocell

Ordering Information:			Part Number:			
*Adder Applies						Ordering Example: WDWSDFWFC-CT-S5-UNV-BZ-ND
Family	ССТ	Optic	Voltage	Finish	Dimming	Accessories*
VVDWSDFWFC	CT - Color Tunable	S5 - Type IV	UNV - 100-277V	BZ - Bronze	ND - Non Dim	EB1 - 8W Emergency Backup Battery EB2 - 15W Emergency Backup Battery EB3 - 20W Emergency Backup Battery



Vivid Leds, Inc. PO BOX 9 Sellersburg, IN 47172 sales@vividleds.us www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Dimensional pictures are for reference only They do not reperesent the actual fixture's shop drawing or design.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.



D8

Architekt FC

Wattage Selectable and Color Tunable Full Cutoff Wall Pack LED Dimmable Luminaire



