

## Product Description

The Twilight series is the leader in the industry for an economical color changing luminaire. Sticking to the basics by using industry standard DMX protocol for control, to clever wiring, to internal self-control with built-in programs, the Twilight series offers a basic solution that applies to even the most difficult applications. With quality throughout, from the LEDs to the die-cast housing, the Twilight shines above the rest.

> Special Order - Minimum 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Edison LEDs with RGBW efficacy >35 Lm/W and white >80 Lm/W\*\*
- Solid state with high shock and vibration resistance
- Dimming capability with DMX or built-in controller
- Each red, green & blue LED has a 256 color depth
- Precise optics with photometric lens built over each LED
- Enhanced 4in1 LED layout under each lens for best light distribution
- Easy installation with 180 degree rotating mounting brackets
- Adjustable mounting brackets can go on the side or bottom of the fixture
- RGBW color changing modes by STICK DE3 DMX 512 controller
- Fixture modes: 1) Independant, 2) DMX, 3) Master/Slave
- LED screen with push button control to change programs or setup DMX
- Built-in self-control with pre-programmed lighting effects
- Programs include solid colors, flashing, fading, color jumping
- High vertical illuminance for large space lighting
- Die-cast 6063 aluminum alloy silver housing with low heat generation
- Durable polycarbonate clear cover with water resistant protection
- Natural convection cooling method
- 5' power cable whip and 1.5' in and out DMX cable standard option
- 1.5' power cable in and out and 1.5' DMX cable in and out linkable option
- Contains no mercury or lead and cool to the touch
- Universal Voltage: 100-277VAC
- Operating temperature: -20 to 40 degrees celsius
- IP65 rated, applicable for indoor or outdoor applications
- 100,000 hour LED life
- Certifications: CE, RoHS, ETL
- 1 Year Warranty – 3 Year Optional

## TWILIGHT Z4

RGBW Color Changing  
LED DMX Wash, Stripe or Graze



### Power & DMX Linkable Option:

DMX Signal Cable with IP68 Connector



Power Cable with IP68 Connector




Power & DMX extension cables  
available on the website

## Models:

- VVDZ4W80L03: 12W - 12" (L) x 3.1" (W) x 4.6" (H) - 4.6 Lbs
- VVDZ4W80L06: 24W - 24" (L) x 3.1" (W) x 4.6" (H) - 7.9 Lbs
- VVDZ4W80L12: 48W - 48" (L) x 3.1" (W) x 4.6" (H) - 12.4 Lbs
- VVDZ4W85L03: 18W - 12" (L) x 3.4" (W) x 6.0" (H) - 5.3 Lbs
- VVDZ4W85L06: 35W - 24" (L) x 3.4" (W) x 6.0" (H) - 8.4 Lbs
- VVDZ4W85L12: 65W - 48" (L) x 3.4" (W) x 6.0" (H) - 13.2 Lbs

Rotating Bracket



Ordering Information:					Part Number:	
*Adder Applies			Ordering Example: VVDZ4W80L03-RGBW1-10-ST-SG-RB			
Family	CCT	Optic	Connection	Finish	Mounting	Accessories*
VVDZ4W80L03 VVDZ4W80L06 VVDZ4W80L12 VVDZ4W85L03 VVDZ4W85L06 VVDZ4W85L12	RGBW0 - RGBW 2700K RGBW1 - RGBW 3000K RGBW2 - RGBW 4000K RGBW3 - RGBW 6500K RGBA - Amber - 2100K*	15 - 15 Degree 30 - 30 Degree 45 - 45 Degree 20 - 20x40 Degree	ST - Standard LK - Linkable*	SG - Silver Gray WT - White* BK - Black* CS - Custom*	RB - Rotating Bracket EA6 - 6" Ext. Arm Pair* EA12 - 12" Ext. Arm Pair* EA18 - 18" Ext. Arm Pair* EA24 - 24" Ext. Arm Pair*	GP - Field Installed Grounded Plug  DMX Cables DMX Controllers Wireless DMX Signal Amplifiers



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
330-809-0431  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

\*\*80 Lm/W is based on 6000K white CCT. Static color or RGB LEDs > 35 Lm/W.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

J8

Revised 4.3.24