Product Description

The Aurora series delivers quality and performance at an affordable price. Utilizing the latest CREE XPE LEDS, the luminaires offer an exceptional efficacy with accurate color projection. Whether you need to replace your existing architectural lighting or install for new construction, Vivid Leds can help you deliver a perfect solution. There are many accessories available to complete the job from start to finish.

| | <u>'</u> | |
|--------------|----------|-------|
| Project: | | Type: |
| Location: | | |
| Prepared By: | | Date: |
| Comments: | | |

Performance Summary

- · CREE XPE LEDS with RGBW efficacy >35 Lm/W and white >80 Lm/W**
- · Provides rich atmosphere with excellent color rendering
- · Solid state with high shock and vibration resistance
- · Dimming capability by any DMX controller
- · Precise optics with photometric lens built over each LED
- Enhanced 4in1 LED layout under each lens for best light distribution
- · Secure installation with 6 wall mount points and easy aiming with screw adjustment
- Includes housing shell to hide inner luminaires
- · Open air top and bottom for heat dissipation and self cleaning
- Rear housing cut out for easy wiring over a recessed electrical box
- · Vandal proof with no option to alter DMX functions
- DMX coding required by Kontrol Master Pro 3 Series
- Kontrol Master Pro 3 sold seperately, only one needed per job
- RGBW color changing modes by STICK DE3 DMX 512 controller
- · High vertical illuminance for large space lighting
- Extruded 6063 aluminum alloy wall mount housing with powdercoat finishes
- · Durable 4mm tempered glass cover on each inner luminaire with water resistant protection
- Pure aluminum inner luminaire with 1.6" depth heatsinks improve thermal property
- · Corrosion resistant, durable, with high efficiency
- 1.5' power cord whip & 1.5' in and out IP68 DMX cables included on each inner luminaire
- Operating temperature: -20 to 40 degrees celsius
- IP65 rated for outdoor applications
- Universal voltage: 100-240 VAC
- · 100,000 hour LED life
- · Certifications: CE, RoHS, ETL
- 1 Year Warranty 3 Year Optional

Models:

- VVDSPD18UW: 18 LEDS 40W Uplight Only 16.5 Lbs
- VVDSPD18DW: 18 LEDS 40W Downlight Only 16.5 Lbs
- VVDSPD18UDW: 36 LEDS 40W Uplight / 40W Downlight 26.4 Lbs

AURORA HOTELIER RGBW

> Special Order - Minimum 30 Day Lead Time

RGBW Color Changing

LED Surface Mount Up/Down Luminaire









| Ordering Information: | | | | Part Number: | | |
|--------------------------------------|--|----------------------------------|----------------|--|-----------------|--|
| *Adder Applies | | | | Ordering Example: VVDSPD9UW-RGBW1-15-UNV-SG-WM | | |
| Family | ССТ | Optic | Voltage | Finish | Mounting | Accessories* |
| WDSPD18UW WDSPD18DW WDSPD18UDW | RGBW1 - RGBW 3000K RGBW2 - RGBW 4300K RGBW3 - RGBW 6000K | 15 - 15 Degree 25 - 25 Degree | UNV - 100-240V | SG - Silver Gray BK - Black WH - White CS - Custom* | WM - Wall Mount | DMX Cables DMX Controllers RGB to DMX IP Coders Wireless DMX Signal Amplifiers Power Cables Waterproof Connectors Transformers |



**80 Lm/W is based on 6000K white CCT. Static color or RGB LEDS > 35 Lm/W.