

Product Description

The Focus TL suspension and surface mount linear LED luminaire provides controlled illumination for general and task lighting designed for the harsh environments found in food processing and heavy manufacturing facilities. The fixture utilizes high efficiency LED light sources to reduce maintenance and lower energy costs. The IP66 waterproof design is an ideal task light to retrofit existing linear fluorescent as well as HID high-bay fixtures.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Energy-efficient Samsung 561B LEDs with high efficacy >130 Lm/W
- USA assembled product with quick warranty support
- In stock and ships from several U.S. locations for quick delivery
- Better visibility than HID with crisp, 4000K or 5000K white light
- Patented design with high quality components, excellent choice for retrofitting
- Heavy duty and high impact resistance
- Solid State with IK10 high-shock and vibration resistance - 3G vibration tested
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Type V 120 degree optic
- High lumen maintenance exceeds DOE requirements
- 1/9th LED micro color binning enables tight color control
- Shatterproof UV-stabilized polycarbonate lens
- Mounting by suspension cable or wall/ceiling bracket
- Heat dissipating powdercoat finish over chromate conversion coating
- Aluminum alloy die cast housing with silicone gaskets
- Housing is sandblasted and polished for corrosion resistance, rust free and fadeless
- Streamlined housing, no rough edges or scraping, with SUS316 stainless steel fasteners
- CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- Replaceable aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Copper condensation valve balances the air pressure and prevents water vapor accumulation
- Cooling fins are added to the heatsink for low temperature and higher efficiency
- Patented double waterproofing design on the radiator and module to prevent condensation
- Advanced constant current Meanwell HLG power supply in integrated junction box
- Electronic Driver, 120-277V 50/60Hz; Less Than 20% THD and PF>0.90
- Standard internal surge protection of 2.5KV
- 0-10V dimming standard for a dimming range of 10% to 100%
- Power input is standard 6' Yellow Cable (5-Conductor Wire to Pigtails) (Black, White, Green, Purple, Gray)
- Excellent optical presentation for multiple applications
- Unmatched thermal management and proven lumen maintenance ratio
- Improved illumination performance and excellent optics control
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- High CRI - RA>80 enhances original colors
- Operating temperature: -20 to 50 degrees celsius
- 100,000 hour LED life - IP66 rated for outdoor locations
- Certifications: CE, RoHS, ETL, cETLus, ANSI/UL, ANSI NSF 2
- 10 year limited warranty

Focus TL

NSF 2 Cold Storage Linear Task Light
LED Dimmable Luminaire



**Surface Bracket
(2 Each Included)**



**Adjustable Cable
(2 Each Included)**



**Wall Mount Bracket
(Order Separately)**



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Applications:

- Low Bay and High Bay
- Food and Beverage Processing
- Food Distribution
- Meat and Poultry Processing
- Livestock Agricultural Facilities
- Heavy Industrial
- Manufacturing Facilities
- Cold Storage
- Vehicle Wash Facilities
- Pharmaceutical and Scientific Labs

Listing & Ratings:

ETL

- Listed for Wet Locations

ANSI/UL

- 1598
- 8750

OTHER


- ETL Sanitation certified to National Sanitation Foundation ANSI NSF2
- Food Splash Zone
- IP66 Sealed LED Compartment
- Pressure wash rated to 1600 PSI
- IK10

Controls:

0-10V dimming standard. Fixtures are NOT designed for use with line voltage dimmers.

NSF 2 – Food Splash Zone

An ETL Sanitation Mark on Food Service Equipment indicates that equipment is tested to ANSI/NSF 2 is fit for use in the production of food intended for human consumption, or the equipment is fit for use in an environment where food intended for human consumption is produced.



Models:

- VDPSN458W - 58W - 7500 Lm - 4' Linear - 49.4" (L) x 3.2" (W) x 4.4" (D)
- VDPSN480W - 80W - 10000 Lm - 4' Linear - 49.4" (L) x 3.2" (W) x 4.4" (D)
- VDPSN880W - 80W - 10000 Lm - 8' Linear - 97.4" (L) x 3.2" (W) x 4.4" (D)
- VDPSN816W - 160W - 20000 Lm - 8' Linear - 97.4" (L) x 3.2" (W) x 4.4" (D)

Ordering Information:

Part Number:

*Adder Applies

Ordering Example: VDPSN458W-40-F-V27-W-

Family	CCT	Optic	Voltage	Housing	Mounting	Accessories*
VDPSN458W VDPSN480W VDPSN880W VDPSN816W	40 - 4000K 50 - 5000K	F - Type V 120 Degrees	V27 - 120-277V	W - White CS - Custom*	SB - Surface Bracket AC - Adjustable Cable WM - Wall Mount Bracket (Set)*	P3 - 3pin Mini Male Plug, 600V, 18A P5 - 5pin Mini Male Plug, 600V, 12A L7 - 15 Amp, 277V, NEMA L7-15P, 2P, 3W, Locking Plug, Industrial Grade, Grounding - Black-White



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

F11

Revised 2.6.23