The Raptor TS Linear Strip has a beautiful round tube design for commercial applications. This fixture combines the latest in LED technology with 125 Lm/W brightness, beautiful light distribution, a commercial grade optic lens. Typical energy savings up to 80% over traditional light sources. Great for retail, supermarkets, hotels, restaurants, offices, showrooms, schools, colleges, and other commercial buildings.

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

Performance Summary

- Philips Lumileds 3030 LEDS with high efficacy >125 Lm/W
- In stock and ships from several U.S. locations for quick delivery
- 8' ships in a 4' box fixtures seamlessly connect together
- Wattage selectable switch allows for a wide range of lumen outputs
- Easy access to control switch for a range of CCT's from 3000K to 5000K
- · Standard design with modern components, excellent choice for retrofitting
- · Slim design blends flat providing a sleek, subtle aesthetic
- · Patented heat dissipation design for optimum efficiency
- Designed with precise tolerances for manufacturing considerations
- National listing lab tested to IES standards with Type V 7H x 7V beam angle
- · High lumen maintenance exceeds DOE requirements
- 0-10V dimming option for enhanced control
- · Solid State with high-shock and vibration resistance
- · Smooth, non-glare and decorative with diffused lens
- Well distributed light using a patented reflecting system
- Effectively illuminates ambient light with superior foot candles
- 3mil thickness aluminum housing with excellent heat dissipation
- · Durable casing with high purity AL6063 aluminum heatsink
- High quality Polystyrene cover with strong capacity
- · Delicate shape, lightweight, easy installation
- · Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- · Architectural white polyester powdercoat finish
- Fast turn on with no warm up or cold start issues
- 1/9th micro color binning enables tight color control
- · Hot color targeting ensures color is within ANSI bin compliance
- Universal 100-277V integral driver with surge protection
- · Silent operation, no noise, no flickering
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 40 degrees C
- 100,000 hour LED life based on LM-80 results and TM-21 calculation
- · Certifications: CE, RoHS, UL, cUL, DLC IP20 outdoor rated
- 10 year limited warranty

Raptor TS

Wattage Selectable and Color Tunable Linear Strip







Models:

- VVDST445P 4' 22W/33W/45W 5467 Lm 3000K/4000K/5000K 48" (L) x 3.03" (H) x -2.65" (W) 80 CRI
- VVDSL8FT6 8' 33W/50W/69W 8624 Lm 3000K/4000K/5000K 96" (L) x 3.03" (H) x -2.65" (W) 80 CRI

Ordering Information:				Part Number:			
*Adder Applies Ordering Example: WDST445P-CT-DF-V27-WT-DI							
Family	сст	Optic	Voltage	Finish	Dimming	Mounting	Accessories*
VVDST445P VVDSL8FT6	CT - Color Tunable	DF - Diffused	V27 - 120-277V	WT - White	DM - 0-10V Dim	SM - Surface Mount	SP - 10KV Surge Protection EM - 8W EM Battery Backup



Vivid Leds, Inc. PO BOX 9 Sellersburg, IN 47172 330-809-0431 www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.