## **Product Description**

The Alume Sign is a UL listed exit sign in an Injection-molded thermoplastic ABS housing in white finish. This general purpose LED exit sign marks exits and hallways towards exits to guide occupants out of commercial and industrial buildings. Applications include Retail, Healthcare, Offices, Education, Commercial Buildings, and Warehouses.

## **Performance Summary**

- Energy-efficient, ultra bright, long life, red or green Samsung LEDS
- Low operating costs and no maintenance
- In stock and ships from several U.S. locations for quick delivery
- National listing lab tested to IES standards
- · Better visibility and longer life than incandescent
- High quality components, excellent choice for retrofitting
- Corrosion resistant enclosure with one piece design
- Injection-molded thermoplastic ABS housing in white finish
- Housing is Impact and scratch resistant
- Mount multiple ways to ceiling or wall with included bracket
- Cutout on backside to mount directly to a wall
- Double waterproofing design to prevent condensation
- UL-94V-0 flame rating, fire-resistant
- Power consumption: 4W max, output: 1W max
- 1.2V long-life, maintenance-free, rechargeable NiCd battery
- Battery discharge time: 90 minutes
- Fully automatic solid-state charger initiates battery to complete recharge in 24 hours
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Solid State with high-shock and vibration resistance
- Patented heat dissipation design for optimum efficiency
- Dual Driver, 120/277V, 50/60Hz
- Operating temperature: 0 to 40 degrees celsius
- IP20 rated for indoor use
- Certifications: CE, RoHS, UL, cUL
- 100,000 hour LED life
- 10 year limited warranty (Excludes Battery)




Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

## Alume Sign







Part Number:

## **Ordering Information:**

*Special Order - Extended Lead Time Applies					Ordering Example: WDLSES037-R-1-EM-W-WB		
Family	Letters	Number of Faces	Voltage/Battery	Housing	Mounting		
VVDLSES037	R - Red G - Green*	1 - Single Face	EM - NiCd 90 Minutes - Dual Circuit with 120V/277V Input	W - White	WB - Wall Bracket		



Vivid Leds, Inc. PO BOX 9 Sellersburg, IN 47172 330-809-0431 www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.