

## Product Description

The Alume Light is a UL listed remote head in an Injection-molded thermoplastic ABS housing in white finish. This general purpose LED light marks exits and hallways towards exits to guide occupants out of commercial and industrial buildings. Applications include Retail, Healthcare, Offices, Education, Commercial Buildings, and Warehouses.

> Quick Ship - In Stock, Ready to Ship


Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Energy-efficient, ultra bright, long life, Samsung LEDs
- Low operating costs and no maintenance
- In stock and ships from several U.S. locations for quick delivery
- National listing lab tested to IES standards
- Better visibility and longer life than incandescent
- High quality components, excellent choice for retrofitting
- Corrosion resistant enclosure with one piece design
- Injection-molded thermoplastic ABS housing in white finish
- Housing is Impact and scratch resistant
- Mount multiple ways to ceiling or wall
- Integrated test switch and charge indicator light
- Double waterproofing design to prevent condensation
- UL-94V-0 flame rating, fire-resistant
- Power consumption: 2W max output
- 3.6V long-life, maintenance-free, rechargeable NiCd battery
- Battery discharge time: 90 minutes
- Fully automatic solid-state charger initiates battery to complete recharge in 24 hours
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Solid State with high-shock and vibration resistance
- Patented heat dissipation design for optimum efficiency
- Dual Driver, 120/277V, 50/60Hz
- Operating temperature: 0 to 40 degrees celsius
- IP20 rated for indoor use
- Certifications: CE, RoHS, UL, cUL
- 100,000 hour LED life
- 10 year limited warranty (Excludes Battery)

## Alume Light

LED Remote Heads



### Models:

- WDLSEML012 - Round
- WDLSEML033 - Square

### Ordering Information:

Part Number:

Ordering Example: WDLSEML012-W-EM

Family	Housing	Voltage/Battery				
WDLSEML012 WDLSEML033	W - White	EM - NiCd 90 Minutes - Dual Circuit with 120V/277V Input				



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
330-809-0431  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

R5

Revised 2.20.23