

Product Description

The Industry series is a vaporproof fixture with a choice of mounting configurations designed to replace HID lighting systems up to 70w MH or HPS. This vapor resistant fixture can withstand extreme physical and environmental abuse and is ideal for retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 8 to 12 feet can be achieved.

> Quick Ship - In Stock, Ready to Ship


Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Samsung LEDs with high efficacy >80 Lm/W
- USA assembled product with quick warranty support
- Standard design with modern components
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Type V optic
- High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Clear heat treated glass globe with diffused option
- A360 extruded ingot die-cast housing and screw on guard with 3/4" NPS
- Repaintable DuPont textured gray architectural powdercoat finish
- Chromate conversion coating for long lasting appearance
- Surface mount design
- Includes weatherproof box with coin plugs
- Rust resistant stainless steel hardware with durable nickel-plating
- High CRI - RA>82 enhances original colors
- 1-10V dimmable driver with surge protection
- Fast turn on with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 40 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 135,000 hour LED life @ L70 tested at 105 degrees celsius
- Certifications: CE, RoHS, CSA, UL - IP66 outdoor rated
- 10 year warranty

INDUSTRY VP

Vaporproof Jelly Jar
LED Dimmable Luminaire



Models:

- WDV43Q: 10W - 836 Lm - 525mA - B:0, U:2, G:0

Ordering Information:				Part Number:		
*Adder Applies		**Adder Applies. Extended Lead Time May Apply.		Ordering Example: WDV43Q-50-S5C-V27-GR-ND		
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories*
WDVB43Q	50 - 5000K 40 - 4000K	S5C - Type V Short 115 Degree	V27 - 120-277V	GR - Gray CS - Custom*	ND - Non Dim DM - 0-10V Dim	SF - Single Fuse DF - Double Fuse VG30F - Diffused Glass Globe VS30A - Angled Stamped Aluminum Shade Gray WG - Wire Guard for Angled Shade PRB1 - Diecast Round Electrical Box with Five 1/2" Coin Plugs RC1 - Backplate with 1/2" Coin Plugs PRB3 - Diecast Round Electrical Box with Five 3/4" Coin Plugs



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

D16