

## Product Description

The Commerce Bell Pendant is available in a Type V distribution with two lens options designed to replace HID lighting systems up to 250w MH or HPS. The fixture mounts to a pole single arm, pole double arm, or wall mount single arm. Typical area lighting applications include parking areas, walkways, and pedestrian public spaces. Mounting heights of 12 to 30 feet can be used based on light level and uniformity requirements.

> Quick Ship - In Stock, Ready to Ship


Project:		Type:	
Location:			
Prepared By:		Date:	
Comments:			

## Performance Summary

- Samsung 351B LEDs >115 Lm/W
- Buy American Act and ARRA compliant
- Quick Ship - In stock and ships from six locations for quick delivery
- USA assembled product with quick warranty support
- National listing lab tested to IES standards
- Photometric optic built over each LED for enhanced light distribution
- Clear prismatic or diffused lens to seal LED array
- Accommodates 3" tenons with wall mount, single pole, or dual pole options
- Pendant mount kit includes top and bottom cover, brackets, 3/4" x 15" downrod
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- A360 extruded ingot sand cast housing
- DuPont architectural powdercoat black finish with custom RAL options
- Decorative spun aluminum shade with black powdercoat finish
- Separate ballast compartment for best heat management
- Integral heat-dissipating fins for thermal management
- Chromate conversion coating for long lasting appearance
- Rust resistant black oxide mounting hardware with durable nickel-plating
- Optional twist-lock receptacle and photocell is installed on arm brackets
- High CRI - RA>80 enhances original colors
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 473,000 hour LED life @ L70 tested at 25 degrees celsius
- Certifications: CE, RoHS, CSA - IP66 sealed LED compartment
- 10 year limited warranty

## COMMERCE BELL

Modern Cast Aluminum Decorative Pole  
LED Dimmable Luminaire



## Models:

- WDAS3037: 37W - 3228 Lm - B:1, U:0, G:1
- WDAS3065: 65W - 5671 Lm - B:2, U:0, G:2
- WDAS3084: 84W - 9614 Lm - B:3, U:3, G:0

Ordering Information:				Part Number:	
*Adder Applies    **Photocell Not Available with Wall Mount				Ordering Example: WDAS30Q1-40-S51-UNV1-SP	
Family	CCT	Optic	Voltage	Mounting	Accessories*
WDAS3037 WDAS3065 WDAS3084	40 - 4000K 50 - 5000K	S51 - Type V Medium Clear Prismatic Lens  S52 - Type V Medium Diffused Lens*  S31 - Type III Clear Prismatic Lens  S32 - Type III Diffused Lens*	UNV1 - 120-277V UNV2 - 347-480V*	SP - Single Pole Arm* DP - Dual Pole Arm* WM - Wall Mount Arm*	CS - Custom Housing Finish SP1 - 20kA Surge Protection 120-277V SP2 - 20kA Surge Protection 347-480V R3 - 3-Pin Twist Lock Receptacle R5 - 5-Pin Twist Lock Receptacle R7 - 7-Pin Twist Lock Receptacle P31 - Twist Lock Non-Shorting Cap (Fixture Always Off) P32 - Twist Lock Shorting Cap (Fixture Always On) P40 - Instant Twist Lock Photocell 110-120 VAC** P50 - Time Delay Twist Lock Photocell 120VAC** P52 - Time Delay Twist Lock Photocell 277 VAC** P57 - Twist Lock Photocell 480 VAC** MS1 - Internal Microwave On/Off Sensor 8' to 19' - 120-277V MS2 - Internal Microwave Dim Sensor up to 40' - 120-277V



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
800-974-3570  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Z54