

Product Description

The Axis series is available with a choice of yoke or slip fitter mounting configurations and medium flood optical distribution designed to replace HID lighting systems up to 400w HID. Typical lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights up to 25 feet based on uniformity requirements.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Samsung LH351Z LEDs with high efficacy >110 Lm/W
- Buy American Act and ARRA compliant
- Quick Ship - In stock and ships from six locations for quick delivery
- USA assembled product with quick warranty support
- National listing lab tested to IES standards
- High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Clear tempered flat glass lens for reduced hot spots
- A360 extruded ingot die-cast housing, front frame and ballast box
- DuPont textured architectural bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- Multiple mounting options available
- Angle indicators on the optional slipfitter assist with proper aiming
- Rust resistant stainless steel hardware with durable nickel-plating
- Hinged front frame for tool-less entry
- High CRI - RA>72 enhances original colors
- 0-10V dimmable driver with surge protection option
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung TZ chip platform with completed 6,000 hour LM-80 test
- 385,000 hour LED life @ L70 tested at 25 degrees celsius
- Certifications: CE, RoHS, CSA - IP65 outdoor rated
- 10 year limited warranty

AXIS 3

Multiple Mounting Options
LED Dimmable Luminaire



Models:

- WDFL65: 68W - 7401 Lm - EPA 1.5

Ordering Information:				Part Number:		
*Adder Applies				Ordering Example: WDFL65-50-S5C-V27-BZ-ND		
Family	CCT	Optic	Voltage	Mounting	Dimming	Accessories*
WDFL65	40 - 4000K 50 - 5000K	S5C - 10 x 140 Degree NEMA 7H x 7V Clear Flat Glass Lens	V27 - 120-277V V48 - 347-480V*	SF - Slipfitter SY - Small Yoke LY - Large Yoke	ND - Non Dim DM - 0-10V Dim	SF - Single Fuse DF - Double Fuse SP - 20kA Surge Protection 120-277VAC PCA - 7-Pin Twist Lock Photocell Receptacle with Shorting Cap PCB - 3-Pin 480V Twist Lock Photocell Receptacle with Cap PC1 - 110-277VAC Instant Twist Lock Photocell PC2 - 120VAC Time Delay Twist Lock Photocell PC3 - 277VAC Time Delay Twist Lock Photocell PC4 - 480VAC Twist Lock Receptacle PC5 - Twist Lock Non-Shorting Open Cap (Fixture Always Off) PC6 - Twist Lock Shorting Cap (Fixture Always On) GS - Aluminum Bronze Glare Shield LG - Clear Polycarbonate Vandal Resistant Guard WG - Stainless Steel Wire Guard SB - 120 Degree Swivel Bronze Wall Bracket with Hardware SPA - Slipfitter with Angle Indicator



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Z78