

## Product Description

This attractive and newly redesigned bollard features an aluminum alloy housing. It provides corrosion and vandal resistance that is not only ideal for lighting pedestrian walkways, but also for accenting the exterior ground of office and apartment buildings, hotels and parks. A solid foundation and driver withstands the elements even in the worst weather conditions. Features a 360 degree surround lens, CCT selectable, and motion sensor.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Alume BL round LED bollard with flat top and 360 degree Lens
- Energy-efficient 2835 SMD LEDs with high efficacy >130 Lm/W
- USA assembled product with quick warranty support
- Dark Sky Compliant - Zero uplight
- In stock and ships from several U.S. locations for quick delivery
- Standard design with modern components, excellent choice for retrofitting
- Low profile, 3G vibration rated compact design minimizes wind loads
- National listing lab tested to IES standards in Type V distribution
- Solid State with high-shock and vibration resistance
- Extruded aluminum tube provides strength and durability
- Versatile anchor bolts allow for easy installation and replacement
- Security screws secure the LED compartment to the base to deter vandalism
- Vented housing isolates LED module from driver, maximizing product life
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Airtight LED compartment to prevent fogging and condensation
- Anodized aluminum reflector reduces glare and produces an even distribution
- Clear UV resistant high-impact polycarbonate lens allows for optimal light output
- Architectural bronze UV-stabilized polyester powdercoat finish
- Chromate conversion coating for long lasting appearance
- Rust resistant stainless steel hardware with durable nickel-plating
- CCT selectable from 3000K, 4000K, or 5000K
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Advanced, serviceable, constant current Sosen driver with 0-10V dimming
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -4 to 40 degrees C
- 100,000 hour LED life based on LM-80 results and TM-21 calculation - RA>80
- Certifications: CE, RoHS, UL, cUL, DLC - IP65 outdoor rated
- 10 year limited warranty

## Alume BL

Ground Mounted with Anchor Bolts  
CCT Selectable LED Luminaire



Versatile anchor bolts  
for any project



## Models:

- VDLSB024W - 24W - 3120 Lm - 0.21A - 42" (H) x 6.3" (W) - 23 Lbs

Ordering Information:				Part Number:			
Ordering Example: VDLSB024W-CS-T5-V27-BZ-FT-CL-AB							
Family	CCT	Optic	Voltage	Finish	Top	Lens Type	Mounting
VDLSB024W	CS - Color Selectable	T5 - Type V 360 Degree	V27 - 120-277V	BZ - Bronze	FT - Flat Top	CL - Clear	AB - Installed Anchor Bolts



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
800-974-3570  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

G21

Revised 9.23.24