Product Description

The Industry series is a ARRA compliant wall mount luminaire using the latest Samsung LEDS. From benchmarking a minimum 104 degree F ambient during thermal testing, to custom designed LED arrays for each luminaire individually, to using the best housing materials and coatings, each aspect has been taken into careful consideration to ensure many years of trouble-free service.

Performance Summary

- Samsung LEDS with high efficacy >135 Lm/W
- Buy American Act and ARRA compliant
- Quick Ship In stock and ships from six locations for guick delivery
- · USA assembled product with quick warranty support
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Type IV optic
- High lumen maintenance exceeds DOE requirements
- · Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Molded prismatic borosilicate glass lens with high quality gasket
- · A360 extruded ingot die-cast housing with hinged semi cutoff front frame
- Includes safety cable to prevent front frame impact when installing
- DuPont textured architectural bronze powdercoat finish
- · Chromate conversion coating for long lasting appearance
- Custom housing colors available upon request
- 1/2" coin plugs with o-rings for conduit and photocell
- Cast-in template for mounting directly over a 4" recessed outlet box
- Accessible to mount by 1/2" surface conduit
- Rust resistant stainless steel hardware with durable nickel-plating
- Fin heatsinks for best heat dissipation and long life
- High CRI RA>84 enhances original colors
- 1-10V dimmable driver with surge protection
- Fast turn on with no warm up or cold start issues
- · Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 129,000 hour LED life @ L70 tested at 25 degrees celsius
- · Certifications: CE, RoHS, CSA IP65 outdoor rated
- 10 year limited warranty

Models:

• WDWPA15FR: 37W - 5045 Lm - 116mA - B:1, U:3, G:3

> Quick Ship - In Stock, Ready to Ship

Project:	Type:
Location:	
Prepared By:	Date:
Comments:	


INDUSTRY SC

Small Semi Cutoff Glass Lens Wall Pack LED Dimmable Luminaire





Swivel Photocell



Ordering Information:			Part Number:			
*Adder Applies **Adder Applies. Extended Lead TIme May				Apply. Ordering Example: VVDWPA15FR-50-S5C-V27-BZ-ND		
Family	ССТ	Optic	Voltage	Finish	Dimming	Accessories*
VVDWPA15FR	50 - 5000K	S4C - Type IV	V27 - 120-277V V28 - 347-480V*	BZ - Bronze CS - Custom**	ND - Non Dim DM - 1-10V Dim	SP - 20kA Surge Protection 120-277VAC EM - Emergency Driver Provides 90 Minutes of Backup Power WG - Stainless Steel Wire Guard P10 - 120V Pencil Photocell 1/2" CdS P12 - 208-277V Pencil Photocell 1/2" CdS P20 - 120V Swivel Photocell 1/2" CdS, Swivels 0-200 Degrees P22 - 208-277V Swivel Photocell 1/2" CdS, Swivels 0-200 Degrees

Pencil Photocell



Vivid Leds, Inc PO BOX 9 Sellersburg, IN 47172 800-974-3570 www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.