

Product Description

The Focus Moonglow is designed to replace HID lighting systems up to 175w MH or HPS. The open door frame allows for maximum light output. Typical applications include office and public buildings, condominiums, schools, shopping malls, and hospitality. Recommended mounting heights are 8 to 20 feet for walls or ceilings.

> Quick Ship - In Stock, Ready to Ship


Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Samsung LEDs with high efficacy >90 Lm/W
- USA assembled product with quick warranty support
- Standard design with modern components, excellent choice for retrofitting
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards with Type IV optic
- High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Diffused low profile polycarbonate opal lens eliminates hot spots
- Round white ABS housing with hinged front frame
- Four clips with tamper resistant screws included
- Excellent resistance to corrosion, UV degradation and abrasion
- High CRI - RA>80 enhances original colors
- 0-10V dimmable driver with surge protection and battery backup option
- Standard 2kV internal surge protection, 20kA optional
- Fast turn on with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 40 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 187,000 hour LED life @ L70 tested at 25 degrees celsius
- Certifications: CE, RoHS, CSA - IP65 outdoor rated
- 10 year limited warranty

FOCUS MOONGLOW

Open Frame Polycarbonate Lens Round Moonglow
LED Dimmable Luminaire



Models:

- WDPR30Q20: 20W - 1869 Lm - B:0, U:4, G:2 - 525 mA - 13.75" (D) x 5.25" (L)
- WDPR32Q30: 30W - 2633 Lm - B:0, U:5, G:3 - 525 mA - 17" (D) x 5.25" (L)

Ordering Information:				Part Number:		
*Adder Applies				Ordering Example: WDPR30Q20-40-S4C-V27-WT-ND		
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories*
WDPR30Q20 WDPR32Q30	40 - 4000K	S4C - Type IV Short	V27 - 120-277V	WT - White	ND - Non Dim DM - 0-10V Dim	MS1 - Internal Microwave On/Off Sensor 8' to 19' - 120-277V MS2 - Internal Microwave Dimming Sensor up to 15' - 120-277V



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

D23

Revised 2.22.22