

Product Description

Cast in a modern and low-profile design, the Array FC is easily customized to fit every building's design aesthetic with a mix of architectural styling and energy savings. Available in two sizes, the Array FC delivers 3,800 to 13,800 lumens with a wide, uniform distribution. It's ideal for illuminating commercial office buildings, warehouses, campuses, shopping malls and other office complexes.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Philips Lumileds 2835 LEDs with high efficacy >140 Lm/W
- USA assembled product with quick warranty support
- In stock and ships from several U.S. locations for quick delivery
- Designed with precise tolerances for manufacturing considerations
- Modern design with modern components, excellent choice for retrofitting
- Low profile, 3G vibration rated compact design prescribed by ANSI C136.31
- National listing lab tested to IES standards with Type IV distribution
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- Rugged one-piece A360 die-cast housing with integral heat sink
- Housing is completely sealed against moisture and environmental contaminants
- External mounting plate makes installation simple and easy
- Architectural polyester bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- Rust resistant stainless steel hardware with durable nickel-plating
- Emergency backup driver optional with 90 minutes of power
- Optional Integrated photocell can be switched on/off on the fixture
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Light engine is color selectable from 3000K, 4000K, and 5000K configurations
- Scalable lumen package adjustments from 100%, 80%, 60%, and 40%
- Photometric optic built over each LED for enhanced light distribution
- Optics are precisely designed to shape the distribution, maximizing efficiency
- High performance UV stabilized optical grade polymer refractor lens
- High CRI - RA>80 enhances original colors
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 104 degrees F (-40 to 40 degrees C)
- 100,000 hour LED life based on LM-80 results and TM-21 calculation
- Certifications: CE, RoHS, UL, cUL, DLC - IP65 outdoor rated
- 10 year limited warranty

ARRAY FC

Wattage & CCT Selectable Full Cutoff Wall Pack
LED Dimmable Luminaire



Models:

- VDWDP1345: 18W/27W/36W/45W - 7,000 Lm - 7.9" (H) x 8.8" (W) x 6.5" (D) - 6 Lbs
- VDWDP1395: 38W/57W/76W/95W - 15,000 Lm - 10.1" (H) x 14.2" (W) x 7.4" (D) - 9.5 Lbs

Ordering Information:				Part Number:		
*Adder Applies				Ordering Example: VDWDP1345-CT-OS-V27-BZ-DM		
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories*
VDWDP1345 VDWDP1395	CT - Color Selectable	T4 - Type IV	V27 - 120-277V	BZ - Bronze	ND - Non-Dim DM - 0-10V Dim	PC - Integrated Switchable Photocell MS - PIR Plug-and-Play Motion Sensor EM - Emergency Battery Backup, 90 Minutes



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

D7

Revised 1.12.25