

Product Description

The Axis UD architectural wall cylinder provides up/down lighting with narrow, medium and wide distributions designed to replace HID lighting systems from up to 100w MH or HPS. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 8 to 16 feet can be achieved.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Samsung COB LEDs with high efficacy >105 Lm/W
- USA assembled product with quick warranty support
- Standard design with modern components, excellent choice for retrofitting
- Patented heat dissipation design for optimum efficiency
- National listing lab tested to IES standards
- High lumen maintenance exceeds DOE requirements
- Photometric optic built over each LED for enhanced light distribution
- Solid State with high-shock and vibration resistance
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Tempered clear flat glass lens on top and bottom
- A360 extruded ingot die-cast housing
- DuPont textured architectural bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- Custom housing colors available upon request
- Mounts directly over a 4" recessed outlet box
- Rust resistant stainless steel hardware with durable nickel-plating
- Fin heatsinks for best heat dissipation and long life
- High CRI - RA>80 enhances original colors
- 0-10V dimmable driver with surge protection option
- Fast turn on with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -40 to 50 degrees celsius
- Samsung chip platform with completed 6,000 hour LM-80 test
- 89,000 hour LED life @ L70 tested at 25 degrees celsius
- Certifications: CE, RoHS, ETL, UL - IP65 outdoor rated
- 10 year limited warranty

Axis UD

Glass Lens Up / Down Turbine Wall Sconce
LED Dimmable Luminaire



Models:

- VDWCTRS: 20W - 2364 Lm - 525mA - B:2, U:1, G:0 - 5.75" (D) x 8.8" (L) x 10.25" (H)
- VDWCTRD: 40W - 4577 Lm - 525mA - B:2, U:5, G:0 - 5.75" (D) x 8.8" (L) x 12.5" (H)

Ordering Information:			Part Number:			
*Adder Applies **Adder Applies. Extended Lead Time.			Ordering Example: VDWCTRS-41-A-V27-BZ-ND			
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories*
VDWCTRS VDWCTRD	41 - 4100K	A = 70° Up / 70° Down B = 100° Up / 100° Down C = 70° Up / 100° Down D = 30° Up / 30° Down E = 30° Up / 100° Down F = 30° Up / 70° Down G = 100° Up / 30° Down H = 100° Up / 70° Down I = 70° Up / 30° Down	V27 - 120-277V	BZ - Bronze BK - Black CS - Custom**	ND - Non Dim DM - 0-10V Dim	SP - 20kA Surge Protection BP - Button Photocell EM - Emergency Driver 90 Minutes



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

D9