

Product Description

With a high performance heat sink, exceptional lumen maintenance, and a rock solid housing, the Exite Pro will last for many years to come. Its power-adjustable options make it a versatile lighting solution that can be customized to fit different settings. With its range of 60-500W, facilities can choose the appropriate power level for their specific needs. With CCT selectable functions, the user can adjust the color temperature easily.

> Special Order - Minimum 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Philips Lumileds Luxeon 2835 2D LEDs with high efficacy up to 160 Lm/W
- National listing lab tested to IES standard with Type V distributions
- Better visibility than HID or fluorescent in 3500K, 4000K, or 5000K selectable CCT
- IK08 tempered clear glass lens for durability and clarity
- Designed for harsh temperature and high humidity
- Solid state with high shock and vibration resistance
- Instant on and off without delay or re-strike
- Industrial die cast fixture housing with high thermal conductivity aluminum
- Smooth electrophoresis powder coat treatment with stainless hardware
- Excellent resistance to corrosion, UV degradation and abrasion
- High quality and efficient thermal heatsinks for long life
- Integrated thread with eyelet for hook, pendant, suspension, or wall/pole bracket
- 10' attached power cord whip - 18AWG*3C 300V/UL/105°
- Commercial CRI - RA>70 enhances original colors (80 optional)
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- No lead, mercury, UV or IR radiation
- Short circuit, over current, over voltage, over temp protection
- Advanced, serviceable, 0-10V dimmable constant current LiFud driver
- Driver has Class 1 protection
- Operating temperature: -40 to 122 degrees F
- IP65 washdown rated for indoor or outdoor applications
- Over 100,000 hour LED life of maintenance-free, safe operation
- Certifications: CE, RoHS, RCM, FCC, TUV, CB, IK08, cUL, UL, DLC
- 10 year limited warranty

EXITE PRO

Multiple Mounting Options

Wattage & CCT Selectable Industrial High Bay
LED Dimmable Luminaire



WVDHB1, WVDHB2, WVDHB3



WVDHB4, WVDHB5



WVDHB6

Models:

- WVDHB1 - 60/80/100W - 9600-16000 Lm - 11" (D) x 4.9" (H) - 4.2 Lbs - M10 Thread
- WVDHB2 - 80/120/150W - 12800-24000 Lm - 11" (D) x 4.9" (H) - 4.2 Lbs - M10 Thread
- WVDHB3 - 120/150/200W - 19200-32000 Lm - 11" (D) x 4.9" (H) - 4.2 Lbs - M10 Thread
- WVDHB4 - 150/200/240W - 24000-38400 Lm - 12.6" (D) x 4.9" (H) - 5.5 Lbs - M10 Thread
- WVDHB5 - 200/240/300W - 32000-48000 Lm - 12.6" (D) x 5.5" (H) - 6.2 Lbs - M10 Thread
- WVDHB6 - 300/400/500W - 48000-80000 Lm - 14.7" (D) x 7.7" (H) - 16.8 Lbs - M12 Thread

Ordering Information:				Part Number:			
*Adder Applies				Ordering Example: WVDHB1-CS-T51-UNV1-BK-ND-IE			
Family	CCT	Optic	Voltage	Finish	Dimming	Mounting	Accessories*
WVDHB1 WVDHB2 WVDHB3 WVDHB4 WVDHB5 WVDHB6	CS - 3000K 4000K 5000K	T51 - Type V 60 Degree T52 - Type V 90 Degree T53 - Type V 120 Degree T54 - Type V 90 Degree Aluminum Reflector* T55 - Type V 120 Degree Polycarbonate Refractor* T56 - Type V 120 Degree Polycarbonate Refractor with bottom dust cover*	UNV1 - 100-277V UNV2 - 277-480V*	BK - Black WT - White* CS - Custom*	ND - No Dim D1 - 0-10V D2 - PWM	IE - Integrated Eyelet CH - Eyelet with 3' 304 Stainless Steel Swing Chain* HK - Integrated 304 Stainless Steel Hook* PM - Conduit (See Thread Size Above) YK - 90 Degree Adjustable Yoke*	SC - 2.5' Stainless Safety CB M10 - M12 to M10 Reducer WG - Wire Guard PR - PIR Sensor MS - Motion Sensor RC - Sensor Remote Control PG1 - 120V Grounded Plug PG2 - 277V NEMA Lock Plug PC6 - 6.5' Power Cord Extension with IP65 Connector (Field Installed) 80 - RA>80 CRI



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

E1

Revised 12.20.24

Accessories:

<p>PIR & MS - PIR & Motion Sensor</p> <ul style="list-style-type: none"> • The fixture includes an expansion port that makes it easy to screw on standard or Lightcloud Blue-enabled PIR and microwave sensors • Sensors can be configured to adjust brightness and hold time, saving additional energy and costs. • A remote is also available for an additional level of control. 		
<p>T54 - Aluminum Reflector</p> <ul style="list-style-type: none"> • Field Installed • 90 Degree Illumination • Spun Aluminum • Includes Stainless Steel Hardware 		
<p>T55 - Polycarbonate Refractor</p> <ul style="list-style-type: none"> • Field Installed • 120 Degree Illumination • Optional Bottom Dust Cover • High impact polycarbonate 		
<p>CH - Eyelet with Swing Chain</p> <ul style="list-style-type: none"> • 3' length chain • 304 Stainless Steel • Eyelet included 		
<p>YK - Adjustable Yoke Bracket</p> <ul style="list-style-type: none"> • Wall or Ceiling Mount • Adjusts 90 Degrees • Powder coat to match fixture housing • Die Cast Aluminum • Stainless Hardware • Field Installed 		
<p>SC - Safety Cable</p> <ul style="list-style-type: none"> • 30" Aircraft Cable • Loop and Clasp Design • Stainless Hardware 		

Accessories:

<p>HK - Stainless Mounting Hook</p> <ul style="list-style-type: none"> • The fixture includes an expansion port that makes it easy to screw on standard or Lightcloud Blue-enabled PIR and microwave sensors • Sensors can be configured to adjust brightness and hold time, saving additional energy and costs. • A remote is also available for an additional level of control. 		
<p>PM - Conduit NPT Mount</p> <ul style="list-style-type: none"> • Field Installed • Use your own conduit • Be aware of M10 or M12 Connection 		
<p>CS - Custom Housing Color</p> <ul style="list-style-type: none"> • Additional Lead Time Applies • Adder Applies • Provide RAL # When Ordering 		