

Product Description

Enhance your indoor lighting with the 4-Foot Alume Wraparound Light by Vivid Leds, featuring adjustable wattage and color temperature. This versatile fixture combines a sleek design with tunable power and CCT options, making it ideal for a variety of applications. Perfect for illuminating a wide range of indoor spaces, such as offices and workspaces, retail environments, educational facilities, warehouses and storage areas.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Philips Lumileds 2835 LEDs with high efficacy >115 Lm/W
- Standard design with modern components, excellent choice for retrofitting
- Low profile, 3G vibration rated in a compact design
- Patented heat dissipation design for optimum efficiency
- Designed with precise tolerances for manufacturing considerations
- National listing lab tested to IES standards with 110 degree beam angle
- High lumen maintenance exceeds DOE requirements
- 0-10V dimming option for enhanced control
- Solid State with high-shock and vibration resistance
- Smooth, non-glare and decorative with diffused lens
- Well distributed light using a patented reflecting system
- Effectively illuminates ambient light with superior foot candles
- Die formed of 0.6mm cold-rolled steel body
- Durable casing with high purity AL6063 aluminum heatsink
- Built with corrosion and rust-proof materials for durability
- High quality Polystyrene cover with strong capacity
- Delicate shape, lightweight, easy installation
- Aluminum LED boards with copper tracings for best thermal management
- LED array manufactured using a state-of-the-art SMT machine
- Light engine is color tunable in a 3500K/4000K/5000K (80 CRI) configuration
- Architectural white polyester powdercoat finish
- Chromate conversion coating for long lasting appearance
- Fast turn on with no warm up or cold start issues
- 1/9th micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Universal 100-277V integral driver
- Silent operation, no noise, no flickering
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Operating temperature: -22 to 104 degrees F
- 100,000 hour LED life based on LM-80 results and TM-21 calculation
- Certifications: CE, RoHS, UL, DLC - IP40 outdoor rated
- 10 year limited warranty

Alume Wrap

Wattage Selectable & Color Tunable 4' Wraparound
LED Dimmable Luminaire



Models:

- VDLSWA50- 4' - 30W/40W/50W - 3450/4600/5750 Lm - 46.8" (L) x 2.8" (H) x -6.9" (W) - 5 Lbs

Ordering Information:				Part Number:			
Ordering Example: VDLSWA50-CT-V27-WT-DM-SK							
Family	CCT	Optic	Voltage	Finish	Dimming	Mounting	Accessories
VDLSWA50	CT - Color Tunable	DF - Diffused	V27 - 120-277V	WT - White	DM - 1-10V Dim	SM - Surface Mounting	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.