

Product Description

The Alume Jelly Jar is easy to install and operate. The light output is soft and uniform thanks to its diffused tempered glass lens. Suitable applications include the garage, bathroom, attic space, basement, lobby, corridor, restaurant, bar, and many more. The heavy duty die cast aluminum housing and silver powder coating will last for years to come.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Energy-efficient Philips Lumileds 2835 SMD LEDS with high efficacy >120 Lm/W
- In stock and ships from several U.S. locations for quick delivery
- Better visibility than HID or fluorescent in 5000K CCT
- Open frame design with NEMA optic of 160 degrees
- Patented design with high quality components, excellent choice for retrofitting
- National listing lab tested to IES standard
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- A360 ingot die-cast aluminum alloy housing with silver gray powdercoat finish
- Streamlined housing, no rough edges or scraping, with 304 stainless steel hardware
- Housing and driver compartment is one piece to maximize heat dissipation
- Angle-adjustable U bracket mount for wall or square pole mounting
- Includes junction box for wiring
- Knockouts on the bottom and sides for NPT conduit
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Well distributed light using a diffused tempered glass reflecting system
- Light output is soft and uniform, providing eye safety
- CNC machined LED boards are flatness controlled for best heat dissipation
- Cooling fins are added to decrease the ambient temperature
- Serviceable constant current Sosen driver
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>80
- Operating temperature: -30 to 45 degrees celsius
- 100,000 hour LED life of maintenance-free, safe operation
- IP65 rated for indoor or outdoor locations
- Certifications: CE, RoHS, UL, cUL, DLC
- 10 year limited warranty

ALUME JELLY JAR

Tempered Glass
LED Luminaire



Models:

- WVDASTJJ: 21W - 2520 Lm - 0.17A - 4" (D) x 8.3" (H) or 12.6" (H with Bracket)

Ordering Information:				Part Number:		
Ordering Example: WVDASTJJ-50-160-V27-SG-ND						
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories
WVDASTJJ	50 - 5000K	160 - NEMA 160 Degree	V27 - 120-277V	SG - Silver Gray	ND - Non Dim	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

F27

Revised 1.4.25

