Product Description

The Alume FWP full cutoff wall pack offers unmatched versatility and performance, making it ideal for commercial and industrial outdoor applications. Illuminate outdoor spaces efficiently with large LED Full Cut-Off Wall Pack Light. With a power 100W and dusk to dawn photocell feature, this light fixture provides bright and energy-saving illumination for outdoor areas.


Project:	Type:
Location:	
Prepared By:	Date:
Comments:	

Performance Summary

- Energy-efficient Philips Lumileds SMD LEDS with high efficacy >140 Lm/W
- In stock and ships from several U.S. locations for guick delivery
- Better visibility than HID with crisp, white light in 5000K CCT
- Open frame design with a Type III IES beam angle
- · Photocell switch to the controls off and on
- · Patented design with high quality components, excellent choice for retrofitting
- · National listing lab tested to IES standard
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- · Aviation grade aluminum alloy die cast housing with bronze powdercoat finish
- Chromate conversion coating for long lasting appearance
- Streamlined housing, no rough edges or scraping, with 304 stainless steel hardware
- · Housing and driver compartment is one piece to maximize heat dissipation
- Wall mount with guick mount back plate for easy installation
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- · Well distributed light using a patented reflecting system
- · CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- UV resistant polycarbonate lens over the LEDS with rubber grommet
- Advanced, serviceable, constant current Sosen driver with 0-10V dimming
- · High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- · Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>80
- Operating temperature: -30 to 45 degrees celsius
- 100,000 hour LED life of maintenance-free, safe operation
- IP65 rated for indoor or outdoor locations
- · Certifications: CE, RoHS, UL, cUL, DLC
- 10 year limited warranty

Models:

• WDFWP100: 100W - 14000 Lm - 14.2" (L) x 9.7" (D) x 9.3" (W)



Alume FWP

> Quick Ship - In Stock, Ready to Ship

Full Cutoff Wall Pack

LED Dimmable Luminaire







Ordering Information:				Part Number:						
Ordering Example: VVDFWP100-50-S3-UNV-BZ-DM-WM-PC										
Family	ССТ	Optic	Voltage	Finish	Dimming	Mounting	Accessories			
VVDFWP100	50 -5000K	S3 - Type III	UNV - 100-277V	BZ - Bronze	DM - 0-10V Dim	WM - Wall Mount	PC - Integrated Photocell			



Vivid Leds, Inc. Sellersburg, IN 47172 sales@vividleds.us www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Dimensional pictures are for reference only. They do not reperesent the actual fixture's shop drawing or design.

