

Product Description

The Alume Light & Sign is a UL listed exit sign in an Injection-molded thermoplastic ABS housing in white finish. The fixture is flame-retardant and has a charge indicator/test button. This general purpose LED exit sign marks exits and hallways towards exits to guide occupants out of commercial and industrial buildings. Applications include retail, healthcare, offices, education, commercial buildings, and warehouses.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Energy-efficient, ultra bright, long life, Samsung LEDs
- Low operating costs and no maintenance
- In stock and ships from several U.S. locations for quick delivery
- Better visibility and longer life than incandescent
- High quality components, excellent choice for retrofitting
- Corrosion resistant enclosure with one piece design
- Injection-molded thermoplastic ABS housing in white finish
- Housing is Impact and scratch resistant
- Mounts to the wall
- Integrated test switch and charge indicator light
- Double waterproofing design to prevent condensation
- UL-94V-0 flame rating, fire-resistant
- Power consumption: 4W max, output: 3.5W max
- 3.6V long-life, maintenance-free, rechargeable NiCd battery
- Battery discharge time: 90 minutes
- Fully automatic solid-state charger initiates battery to complete recharge in 24 hours
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Solid State with high-shock and vibration resistance
- Patented heat dissipation design for optimum efficiency
- Dual Driver, 120/277V, 50/60Hz
- Operating temperature: 0 to 40 degrees celsius
- IP20 rated for indoor use
- Certifications: CE, RoHS, UL, cUL
- 100,000 hour LED life
- 5 year limited warranty (Excludes Battery)

Alume Light & Sign

LED Exit Sign with Remote Heads



Models:

- VDLSES7SR - Red Letters - Round Lights - White Housing - 11.8" (W) x 7.3" (H) x 1.8" (D)
- VDLSES7SG - Green Letters - Round Lights - White Housing 11.8" (W) x 7.3" (H) x 1.8" (D)
- VDLSES082 - Red letters - Square Lights - White Housing - 19.6" (W) x 7.3" (H) x 1.8" (D)
- VDLSES075 - Red letters - Round Lights - Black Housing - 11.7" (W) x 7.4" (H) x 1.8" (D)

Ordering Information:

Part Number:

Ordering Example: VDLSES7SR-W-EM

Family	Housing	Voltage/Battery				
VDLSES7SR VDLSES7SG VDLSES082 VDLSES075	W - White	EM - NiCd 90 Minutes - Dual Circuit with 120V/277V Input				



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and
product pictures are subject to
change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

R6

Revised 5.2.25