

## Product Description

The Alume Edge is a modern designed edge lit red exit sign that combines sleek aesthetics with reliable performance, making it the most versatile exit sign on the market. Perfect for a variety of environments, it ensures clear visibility and direction during emergencies. Flexible installation with wall, sloped, high, standard ceiling, and recessed mount options.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Energy-efficient and ultra bright Samsung LEDs
- Long-life LED lights ensure bright, energy-efficient illumination
- Low operating costs and no maintenance
- In stock and ships from several U.S. locations for quick delivery
- Better visibility and longer life than incandescent
- High quality components, excellent choice for retrofitting
- Instant illumination and restrike with no warm up or cold start issues
- Solid State with high-shock and vibration resistance
- Ideal for offices, retail stores, and other commercial spaces
- Ensures safe egress in schools, colleges, and universities
- Provides essential emergency lighting in hospitals, clinics, and care centers
- Suitable for use in government buildings, libraries, and other public facilities
- Corrosion resistant enclosure with one piece design
- Double waterproofing design to prevent condensation
- UL-94V-0 flame rating, fire-resistant
- Aluminum housing with a high-grade acrylic face for a sleek and professional look
- Housing is Impact and scratch resistant
- Mount multiple ways to ceiling, wall, or recessed
- Field installable arrows for left, right, or both directions, allowing for tailored installation
- Power consumption: 2W max, output: 1-2W max
- 1.2V long-life, maintenance-free, rechargeable NiCd battery
- Battery discharge time: 90 minutes
- Fully automatic solid-state charger initiates battery to complete recharge in 24 hours
- Test switch and charge rate indicator for reliable operation in battery backup mode
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Patented heat dissipation design for optimum efficiency
- Dual Driver, 120/277V, 50/60Hz
- Operating temperature: 0 to 40 degrees celsius
- Listed for use in damp locations, providing reliable performance in various conditions
- Certifications: RoHS, UL 924, NEC, OSHA, and NFPA 101 Life Safety Code standards
- 100,000 hour LED life
- 5 year limited warranty (Excludes Battery)

## Alume Edge

Edge Lit LED Exit Sign



## Ordering Information:

Part Number:

Ordering Example: VDWLSGL03YR-R-EM

Family	Letters	Voltage/Battery				
VDWLSGL03YR	R - Red	EM - NiCd 90 Minutes - Dual Circuit with 120V/277V Input				



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
330-809-0431  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

R7

Revised 5.2.25