

Product Description

The Alume Bullet flood light is perfect for landscape lighting around outdoor basketball courts, tennis courts, the school playground, community areas, warehouses, factories, gymnasiums or supermarkets. With an acceptable 3375 lumen LED and color selectable range, it can be used in many applications. Its easy to install with a swivel adjustable knuckle arm mount. Expect long life with its die-cast aluminum housing.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Energy-efficient Philips Lumileds 2835 SMD LEDs with high efficacy >130 Lm/W
- In stock and ships from several U.S. locations for quick delivery
- Easy access to control switch for a range of CCT's from 3000K, 4000K or 5000K
- Open frame design with NEMA optic of 38 degrees
- Patented design with high quality components, excellent choice for retrofitting
- National listing lab tested to IES standard
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- A360 ingot die-cast aluminum alloy housing with bronze powdercoat finish
- Streamlined housing, no rough edges or scraping, with 304 stainless steel hardware
- Housing and driver compartment is one piece to maximize heat dissipation
- 1/2" adjustable swivel knuckle arm mount for easy installation and retrofits
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Well distributed light using a patented reflecting system
- Light output is soft and uniform, providing eye safety
- The optic is built over each LED for precision output
- CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- Cooling fins are added to decrease the ambient temperature
- Shatterproof polycarbonate optical lens over the LEDs with rubber grommet
- Serviceable constant current 0-10V dimmable Sosen driver
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>72
- Operating temperature: -40 to 45 degrees celsius
- 100,000 hour LED life of maintenance-free, safe operation
- IP65 rated for indoor or outdoor locations
- Certifications: CE, RoHS, UL, cUL, DLC
- 10 year limited warranty

ALUME BULLET

Color Selectable with an Adjustable Knuckle
LED Luminaire



Models:

- WDASTFL17: 25W - 3375 Lm - 0.2A - 3500K/4000K/5000K - 4" (D) x 6.3" (W)

Ordering Information:				Part Number:		
Ordering Example: WDASTFL17-CS-38-V27-BZ-ND						
Family	CCT	Optic	Voltage	Finish	Dimming	Accessories
WDASTFL17	CS - 3000K 4000K 5000K	38 - NEMA 38 Degree	V27 - 120-277V	BZ - Bronze	ND - Non Dim D1 - 0-10V	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

B5

Revised 3.4.26

