

## Product Description

The Alume RC is specifically designed for garage lighting. By using a die cast aluminum alloy housing, anti-corrosion painting, and IP65 design, this fixture is great for MH / HPS garage and canopy lighting replacement. The completed LED canopy can work up to 100,000 hours, saving up to 80% energy, and have better lighting characteristics than a traditional metal halide lamp up to 250W.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary

- Energy-efficient Philips Lumileds SMD LEDs with high efficacy >130 Lm/W
- Three way wattage selectable up to 7800 Lumens
- USA assembled product with quick warranty support
- In stock and ships from several U.S. locations for quick delivery
- Better visibility than HID or fluorescent with crisp, white light in 5000K CCT
- Open frame design with Type V IES 110 degree beam angle
- Optional motion sensor
- Patented design with high quality components, excellent choice for retrofitting
- National listing lab tested to IES standard
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- A360 ingot die-cast aluminum alloy housing with white powdercoat finish
- Streamlined housing, no rough edges or scraping, with 304 stainless steel hardware
- Housing and driver compartment is one piece to maximize heat dissipation
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- Cooling fins are added to decrease the ambient temperature
- Shatterproof polycarbonate lens over the LEDs with rubber grommet
- Serviceable constant current Sosen driver with integrated 10KV surge protection
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>70
- Operating temperature: -40 to 45 degrees celsius
- 100,000 hour LED life of maintenance-free, safe operation
- IP65 rated for indoor or outdoor locations
- Certifications: CE, RoHS, ETL, cETL, DLC
- 10 year limited warranty

## Alume RC

Wattage Selectable Surface Mount Canopy  
LED Luminaire



## Models:

- VD3NCP60WS: Wattage Selectable - 30W/40W/60W - 7800 Lm - 11.4" (D) x 4.5" (H) - 5.3 Lbs

Ordering Information:				Part Number:		
*Adder Applies		**VVD3NCP60WS Only		Ordering Example: VD3NCP60WS-50-S5-UNV-WT-ND-SM1		
Family	CCT	Optic	Voltage	Finish	Accessories*	Mounting
VD3NCP60WS	50 - 5000K	S5 - 110 Degree	UNV - 100-277V	WT - White	MS - Motion Sensor**	SM1 - Surface Mount with J-Box SM2 - Surface Mount with Side Wiring PM - Pendant Installation with 3/4" Conduit



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
sales@vividleds.us  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

C3

Revised 9.1.23