

Product Description

Alume WPR LED wall pack is designed with rotatable light heads to adjust the the light output to the right spot. The Alume replaces traditional MH / HPS wall packs using well sealed die-cast aluminum housings and polycarbonate lenses. The Alume is easy to install and has a dimming function available. Replace your MH / HPS wall packs up to 400W with the latest technology in lighting - the Alume WPP!

> Quick Ship - In Stock, Ready to Ship

Project:		Type:	
Location:			
Prepared By:		Date:	
Comments:			

Performance Summary

- Energy-efficient Philips Lumileds SMD LEDs with high efficacy >130 Lm/W
- USA assembled product with quick warranty support
- In stock and ships from several U.S. locations for quick delivery
- Better visibility than HID or fluorescent with crisp, 5000K white light
- Open frame design with Type V IES 60 degree rotatable beam angle
- Patented design with high quality components, excellent choice for retrofitting
- National listing lab tested to IES standard
- High lumen maintenance exceeds DOE requirements
- Solid State with high-shock and vibration resistance
- Aviation grade aluminum alloy die cast housing with bronze powdercoat finish
- Chromate conversion anti-corrosion coating for long lasting appearance
- Streamlined housing, no rough edges or scraping, with 304 stainless steel hardware
- Housing and driver compartment is one piece to maximize heat dissipation
- Innovative quick mount bracket for easy, contractor friendly installation
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- CNC machined LED boards are flatness controlled to 0.1mm to speed up heat dissipation
- High quality and efficient thermal heatsinks for long life
- Shatterproof polycarbonate lens over the LEDs with rubber grommet
- Advanced, serviceable, constant current dimmable Sosen driver
- High power factor with IC controlled LED circuits and low THD driver
- Low junction temperature for long life and low lumen depreciation
- Instant illumination and restrike with no warm up or cold start issues
- Contains no mercury, lead, infrared or UV radiation and cool to the touch
- Commercial CRI: RA>70
- Operating temperature: -40 to 40 degrees celsius
- 100,000 hour LED life of maintenance-free, safe operation
- IP65 rated for indoor or outdoor locations
- Certifications: CE, RoHS,UL, cUL, DLC
- 10 year limited warranty


Alume WPR

Rotatable Polycarbonate Lens Wall Pack
LED Dimmable Luminaire



Models:

- VDWDP40WV2: 40W - 4800 Lm - 18 Lbs
- VDWDP80WV2: 80W - 10400 Lm - 22 Lbs
- VDWDP120WV2: 120W - 15600 Lm - 28 Lbs



Ordering Information:				Part Number:			
*Adder Applies				Ordering Example: VDWDP80WV2-50-S5-UNV-BZ-DM-WM			
Family	CCT	Optic	Voltage	Finish	Dimming	Mounting	
VDWDP40WV2 VDWDP80WV2 VDWDP120WV2	50 - 5000K	S5 - Type V 60 Degree	UNV - 100-277V	BZ - Bronze	DM - 0-10V Dim	WM - Wall Mount	



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
sales@vividleds.us
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

Dimensional pictures are for reference only. They do not represent the actual fixture's shop drawing or design.

D8