

## Product Description

The Kontrol Signal DMX Series is a signal amplifier that can withstand the elements. With a IP65 rating, it can be outdoors within your application for long DMX runs over 300'. With matching waterproof connectors to our Twilight fixtures, this amplifier can simply connect in line with other fixtures.

> Special Order - Minimum 30 Day Lead Time

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

## Performance Summary


- Strong adaptability, high reliability and small size
- Opto-coupler isolation between I/O signal
- Synchronizes multiple RGB LED lighting fixtures
- Quick installation with wall or ground mounting
- Install an amplifier every 300' for best signal operation
- Install an amplifier every 60 fixtures
- IP68 male and female I/O signal cables
- Plug-n-play system
- Microcomputer control technology
- Meets DMX 512 protocols
- Repeats signal to control for an unlimited amount of
- Real-time color and effect changes
- Settings take effect immediately without re-power
- Power consumption: 2W
- Voltage: 100-277 VAC
- Dimensions: 7.9"(L) x 3.7"(W) x 2.4"(H)
- Weight: 3.3 Lbs
- Operating temperature: -20 to +40C
- IP65 Rated for outdoor applications

## KONTROL SIGNAL DMX


Maintains Optimal Signal For Long DMX Runs  
LED DMX Signal Amplifier



### Installation:



Standard DMX512 signal amplifier, one input & one output connector: XLR-3



## Ordering Information:

Part Number:

\*Adder Applies

Ordering Example: VVD505-120-WT-WM

Family	Voltage	Finish	Mounting	Accessories*
VVD505	UNV - 100-277 VAC	WT - White	WM - Wall Mount	DMX Cables DMX Controllers Wireless DMX



Vivid Leds, Inc.  
PO BOX 9  
Sellersburg, IN 47172  
330-809-0431  
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

L3