

Product Description

The Alume Straight Square Steel Direct Burial poles are built from high strength steel tube and are available side drilled for arm mounted area lighting luminaires or with tenon mounts for flood and post top luminaires. Typical area lighting applications include retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 20' to 25'.

> Quick Ship - In Stock, Ready to Ship

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

Performance Summary

- Dallas, TX and Temecula, CA warehoused product with same day shipping
- Hand hole and cover included
- Polycarbonate top cover and hole plugs for unused drilling locations
- Poles are pre-drilled for side mount
- Drill templates available for a variety of luminaire mounting options
- Die cast aluminum reinforced cast iron hand-hole and cover with ground screw
- Anchor bolts are Included and sized based on selected pole size
- Conforms to ASTM-A 500 Grade B: minimum yield strength of 46,000 PSI
- Galvanized steel with 11 gauge (.120") wall thickness
- Textured architectural polyester powdercoat finish
- Black Asphaltum applied for best below grade corrosion resistance
- Baked to ensure maximum paint adhesion, hardness and durability
- Custom length pole height cutting is available

ALUME DIRECT BURIAL

Straight Square Steel Poles



Models:

- WDP20F3DB: Up to 20 foot (25 foot total), 4 inch square, 9.5" bolt circle, 10.5" base size, 1" base thickness, 4" bolt projection
- WDP25F3DB: Up to 25 foot (30 foot total), 4 inch square, 9.5" bolt circle, 10.5" base size, 1" base thickness, 4" bolt projection

Ordering Information:			Part Number:		
*Adder Applies. Extended Lead Time Applies.			Ordering Example: WDP20F3DB-20-BZ		
Family	Pole Height***	Housing Finish			Accessories
WDP20F3DB WDP25F3DB	20 - 20 Foot 25 - 25 Foot CS - Custom*	BZ - Bronze			SEE NEXT PAGE

***Pole Height is Below Ground Measurement



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

Accessories for 4" Straight Square Steel Pole:

<p>VVDPTS1S1SZ - Single Spoke Bracket, fits P2 Tenon</p> 	<p>VVDPTS290SZ - Twin Spoke Bracket, 90 Degree Arms, fits P2 Tenon</p> 	<p>VVDPTS2180SZ - Twin Spoke Bracket, 180 Degree Arms, fits P2 Tenon</p> 
<p>VVDPTS390SZ - Triple Spoke Bracket, 90 Degree Arms, fits P2 Tenon</p> 	<p>VVDPTS3120SZ - Triple Spoke Bracket, 120 Degree Arms, fits P2 Tenon</p> 	<p>VVDPTS490SZ - Quad Spoke Bracket, 90 Degree Arms, fits P2 Tenon</p> 
<p>VVDPRSTR180BHZ - 180 Degree Triple Bullhorn, 30 1/4" Span between mounting points, fits P2 Tenon</p> 	<p>VVDPRSQ180BHZ - 180 Degree Quad Bullhorn, 30 1/4" Span between mounting points, fits P2 Tenon</p> 	<p>VVDPRSD180BHZ - 180 Degree Double Bullhorn, 42 7/8" Span between mounting points, fits P2 Tenon</p> 
<p>VVDPSS4TRVTZ - Triple Square Vertical Tenon, 26" Span between mounting points, fits P2 Tenon</p> 	<p>VVDPSS4Q180VTZ - Quad Square Vertical Tenon, 180 Degree, 26" Span between mounting points, fits P2 Tenon</p> 	<p>VVDPSS4Q0VTZ - Quad Square Vertical Tenon, 90 Degree, 26" Span between mounting points, fits P2 Tenon</p> 
<p>VVDPSS4TVTZ - Twin Square Vertical Tenon, 26" Span between mounting points, fits P2 Tenon</p> 	<p>VVDPSS4T180HTZ - Twin Square Horizontal Tenon, 180 Degree</p> 	<p>VVDPSS4T90HTZ - Twin Square Horizontal Tenon, 90 Degree</p> 
<p>VVDPSS4TR90HTZ - Triple Square Horizontal Tenon, 90 Degree</p> 	<p>VVDPSS4Q90HTZ - Quad Square Horizontal Tenon, 90 Degree</p> 	<p>VVDPRSWMBZ - Wall Mount Bracket</p> 



Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
800-974-3570
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.