Product Description

> Special Order - Minimum 30 Day Lead Time

The Twilight X8 is the leader in the industry for an economical color changing luminaire. Sticking to the basics by using industry standard DMX protocal for control, to clever wiring, to internal self-control with built-in programs, the Twilight X8 offers a basic solution that applies to even the most difficult applications. With quality throughout, from the LEDS to the die-cast housing, the Twilight shines above the rest.

Project:		Type:
Location:		
Prepared By:		Date:
Comments:		

TWILIGHT X8

Static Color, Static White, RGB, RGBW Color Changing

LED DMX Wash, Stripe, Spot or Graze

Performance Summary


- Edison LEDS with RGB efficacy >35 Lm/W and white >80 Lm/W**
- Incredible light throw with 5 degree optic lens up to 325 feet
- Provides rich atmosphere with excellent color rendering
- DMX / RDM integrated into the fixture
- Each red, green & blue LED has a 256 color depth
- Precise optics with photometric lens built over each LED
- 1/9th LED micro color binning enables tight color control
- Hot color targeting ensures color is within ANSI bin compliance
- Ground mounted attached base secures with four bolts
- Easy installation and aiming with 80 degree rotating vertical brackets
- Double head and double angle design can adapt to different building heights
- DMX / RDM integrated into the fixture
- Static color or white option dimming and on/off control requi
- RGB or RGBW color changing modes by DMX / RDM controlle
- LED screen with push button control to change programs or
- Built-in self-control with pre-programmed lighting effects
- Extruded 6063 aluminum & iron housing with low heat gener
- Durable polycarbonate clear cover with water resistant prote
- Corrosion resistant, durable, with high efficiency
- 5' power cord whip & 1.5' in and out IP68 DMX cables include
- Contains no mercury or lead and cool to the touch
- Solid state with high shock and vibration resistance
- Operating temperature: -20 to 40 degrees celsius
- IP65 rated for outdoor applications
- 100,000 hour LED life
- Certifications: CE, RoHS, ETL
- 1 Year Warranty – 3 Year Optional





Dual Head with Independent Vertical Rotation

Weight 94 Lbs



Models:

- VVDX8144RGBWV: 144 LEDS - 500W - RGBW - 5, 10, 20, 45 Degree - 26.7" (W) x 17.3" (H)
- VVDX8216RGBV: 216 LEDS - 500W - RGB - 5, 15, 30, 45 Degree - 26.7" (W) x 17.3" (H)
- VVDX8216SV: 216 LEDS - 500W - Static color or white - 5, 15, 30, 45 Degree - 26.7" (W) x 17.3" (H)

Ordering Information:

Part Number:

*Adder Applies

Ordering Example: VVDX8144RGBWV-RGBW1-10-UNV-SG-GB

Family	CCT	Optic	Voltage	Finish	Mounting	Accessories*
VVDX8144RGBWV VVDX8216RGBV VVDX8216SV	RGB - RGB Color Changing RGBW1 - RGBW 3000K RGBW2 - RGBW 4000K RGBW3 - RGBW 6000K W - Static White - 3000K N - Static White - 4300K C - Static White - 6000K R - Static Red - 625nm G - Static Green - 525nm B - Static Blue - 460nm Y - Static Yellow/Amber - 590nm	5 - 5 Degree* 10 - 10 Degree 15 - 15 Degree 20 - 20 Degree 30 - 30 Degree 45 - 45 Degree	UNV - 120 - 277V	SG - Silver Gray CS - Custom*	GB - Ground Base	GP - Field Installed Grounded Plug DM - Static DMX Dim DMX Cables DMX Controllers Wireless DMX Signal Amplifiers

**80 Lm/W is based on 6000K white CCT. Static color or RGB LEDS > 35 Lm/W.

VividLeds
ILLUMINATING YOUR GREEN FUTURE

Vivid Leds, Inc.
PO BOX 9
Sellersburg, IN 47172
330-809-0431
www.vividleds.us

Dimensions, specifications, and product pictures are subject to change without notice.

The product on this page is a manufactured to order, non-stocking item. This product cannot be returned for refund or credit.

Revised 10.14.26